


Product: RUBIN CLEAN NO FRAME LED CRI95 10800 MICRO-PRM SH EDD IP65 34 940 / 1174X574MM

Index: 19.4076.1543.34



Description

Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaires (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering „deep red” color, and R13 responsible for rendering „light orange” color). Surface mounted luminary equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body.

Product information


Category	Clean luminaires CRI95
Family	RUBIN CLEAN NO FRAME LED CRI95
Name	RUBIN CLEAN NO FRAME LED CRI95 10800 MICRO-PRM SH EDD IP65 34 940 / 1174X574MM
Index	19.4076.1543.34
EAN	5902107489885



Light and electrical data



Light source	LED
Luminous flux LED [lm]	12426
LED power [W]	72,6
Luminaire luminous flux [lm]	9108
Power of luminaire [W]	81,3
Luminaire's light efficiency [lm/W]	112
Color of the light [K]	4000
CRI	>95
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	7 (B10), 11 (B16), 11 (C10), 17 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass)
Impact resistant	IK08
Dimensions [mm]	1174 x 574 x 69

A graph of light



Accessories

Index 6BZBO60980

Name Handle for pane opening

