

Product: RUBIN CLEAN NO FRAME LED CRI95 3600 SHM E IP65 34 940 / 574X274MM

Index: 19.4076.2141.34



Description

Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaires (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminaire recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering „deep red” color, and R13 responsible for rendering „light orange” color). Surface mounted luminaire equipped in highly efficient LED panels. Luminaire body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminaire body.

Product information

Category	Clean luminaires CRI95
Family	RUBIN CLEAN NO FRAME LED CRI95
Name	RUBIN CLEAN NO FRAME LED CRI95 3600 SHM E IP65 34 940 / 574X274MM
Index	19.4076.2141.34
EAN	5901867494658



Light and electrical data

Light source	LED
Luminous flux LED [lm]	4142
LED power [W]	24,2
Luminaire luminous flux [lm]	3276
Power of luminaire [W]	27,1
Luminaire's light efficiency [lm/W]	120,9
Color of the light [K]	4000
CRI	>95
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	SHM (hardened mat glass)
Impact resistant	IK08
Dimensions [mm]	574 x 274 x 69

A graph of light



Accessories

Index 6BZBO60980
 Name Handle for pane opening

