

Product: AGAT CLEAN CLASS 5-6 LED 6500 SLM E IP65 840 KRG3K / 600X600

Index: 19.4079.4221.34



Description

Luminary dedicated for the clean rooms of increased cleanliness class ISO 5-6. Luminary designed to module suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white.

Product information

Category	Clean Class 3-9
Family	AGAT CLEAN CLASS 5-6 LED
Name	AGAT CLEAN CLASS 5-6 LED 6500 SLM E IP65 840 KRG3K / 600X600
Index	19.4079.4221.34



Light and electrical data

Light source	LED
Luminous flux LED [lm]	6543
LED power [W]	33,3
Luminaire luminous flux [lm]	5242
Power of luminaire [W]	34,8
Luminaire's light efficiency [lm/W]	150,6
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 100° / 100,2°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)

Mechanical data



Assembly	mounted in module ceilings
Material	steel sheet
Color	white
Diffuser	SLM (laminated mat glass)
Impact resistant	IK08
Dimensions [mm]	596 x 596 x 76

A graph of light

