

Product: AGAT CLEAN CLASS 5-6 LED 6600 SLM E IP65 34 840 KRG3K / 600x600

Index: 19.4079.4321.34



Description

Luminary dedicated for the clean rooms of increased cleanliness class ISO 5-6. Luminary designed to module suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white.

Product information

| | |
|----------|---|
| Category | Clean Class 3-9 |
| Family | AGAT CLEAN CLASS 5-6 LED |
| Name | AGAT CLEAN CLASS 5-6 LED 6600 SLM E IP65 34 840 KRG3K / 600x600 |
| Index | 19.4079.4321.34 |
| EAN | 5901867419361 |



Light and electrical data

| | |
|---|--|
| Light source | LED |
| Luminous flux LED [lm] | 7013 |
| LED power [W] | 32,7 |
| Luminaire luminous flux [lm] | 5056 |
| Power of luminaire [W] | 36,6 |
| Luminaire's light efficiency [lm/W] | 138,1 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 109,6° / 109,6° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP65 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 100000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | standard on/off (E) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 25 (B10), 40 (B16), 39 (C10), 62 (C16) |

Mechanical data



| | |
|--------------------|---|
| Assembly | mounted in module ceilings, as well as plasterboard ceilings |
| Material | steel sheet |
| Color | RAL 9016 (white) |
| Diffuser | SLM (laminated mat glass) |
| Impact resistant | IK08 |
| Dimensions [mm] | 596 x 596 x 76 |
| Mounting hole [mm] | 580 x 580 |

A graph of light

