

Product: AGAT CLEAN CLASS 5-6 LED 5200 MICRO-PRM SL EDD IP65 34 840 KRG5DK / 600X600

Index: 19.4079.2123.34



Description

Luminary dedicated for the clean rooms of increased cleanliness class ISO 5-6. Luminary designed to module suspended ceilings, equipped with the highly efficient LED panels. Luminary body made from steel sheet, powder coated in white.

Product information

| | |
|----------|---|
| Category | Clean Class 3-9 |
| Family | AGAT CLEAN CLASS 5-6 LED |
| Name | AGAT CLEAN CLASS 5-6 LED 5200 MICRO-PRM SL EDD IP65 34 840 KRG5DK / 600X600 |
| Index | 19.4079.2123.34 |
| EAN | 5902107086022 |



Light and electrical data

| | |
|---|--|
| Light source | LED |
| Luminous flux LED [lm] | 5343 |
| LED power [W] | 24,8 |
| Luminaire luminous flux [lm] | 3927 |
| Power of luminaire [W] | 27,8 |
| Luminaire's light efficiency [lm/W] | 141,3 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 89° / 89° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP65 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 100000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | DIM DALI (EDD) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 17 (B10), 28 (B16), 26 (C10), 41 (C16) |

Mechanical data



| | |
|--------------------|---|
| Assembly | mounted in module ceilings, as well as plasterboard ceilings |
| Material | steel sheet |
| Color | RAL 9016 (white) |
| Diffuser | Micro-PRM SL (micro-prismatic diffuser PMMA with laminated glass) |
| Impact resistant | IK08 |
| Dimensions [mm] | 596 x 596 x 76 |
| Mounting hole [mm] | 580 x 580 |

A graph of light

