

**Product:** AGAT CLEAN CLASS 5-6 NO FRAME LED 6600 MICRO-PRM SH E IP65 34 830 KRG3K / 600X600

**Index:** 19.4082.1311.34



## Description

Luminary dedicated for the clean rooms of increased cleanliness class ISO 5-6. Luminary designed to module suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body.

## Product information

Category	Clean Class 3-9
Family	AGAT CLEAN CLASS 5-6 NO FRAME LED
Name	AGAT CLEAN CLASS 5-6 NO FRAME LED 6600 MICRO-PRM SH E IP65 34 830 KRG3K / 600X600
Index	19.4082.1311.34
EAN	5901867420459



## Light and electrical data


Light source	LED
Luminous flux LED [lm]	6663
LED power [W]	32,7
Luminaire luminous flux [lm]	4884
Power of luminaire [W]	36,6
Luminaire's light efficiency [lm/W]	133,4
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)

Mechanical data



Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass)
Impact resistant	IK08
Weight [kg]	7,7
Dimensions [mm]	596 x 596 x 76
Mounting hole [mm]	580 x 580

A graph of light



Accessories

Index	6BZBO60980
Name	Handle for pane opening

