

Product: X-LINE SLIGHT L-DOWN LED 1300 MICRO-PRM E 24 830 / L-572MM S-1,5M

Index: 19.4085.5111.24



Description

Linear luminaire with minimized width. Made of 34 mm wide and 68 mm high aluminum profile. Mounted on slings. Direct light distribution. The optical system is fulfilled by an aperture recessed into the body, facing the end cap. Available opal smooth or microprismatic diffuser made of PMMA. Luminaire in single version. Available colours: anodized aluminum, black (RAL 9005), grey (RAL 9006), white (RAL 9016) or any RAL colour on request. End cap aluminum, painted in the colour of the body. Application of luminaires typically for offices, public spaces, community areas in multi-family buildings. Selected luminaire variants can be fitted with a sound-absorbing housing.

Product information

Category	Surface mounted luminaires
Family	X-LINE SLIGHT LED
Name	X-LINE SLIGHT L-DOWN LED 1300 MICRO-PRM E 24 830 / L- 572MM S-1,5M
Index	19 4085 5111 24
















Light and electrical data

Light course	LED	
Light source		
Luminous flux LED [lm]	1403,7	
LED power [W]	6,9	
Luminaire luminous flux [lm]	1144	
Power of luminaire [W]	8,6	
Luminaire's light efficiency [lm/W]	133	
Color of the light [K]	3000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 86,2° / 111°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP40	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	145000	
Lx/By	L90/B10	
Operating temperature range [°C]	5 ÷ 35	
Driver	standard on/off (E)	
Power factor cos φ	>0,95	
Circuit load capacity	23 (B10), 36 (B16), 35 (C10), 60 (C16)	




$\mathbf{R}\mathbf{A}\mathbf{A}$	NAK	SIC	100	data
IVIT	-(-1	ıalı	III.di	data





Assembly	surface mounted on slings
Material	aluminum
Color	anodised aluminum
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Weight [kg]	1,9
Dimensions [mm]	572 x 34 x 68

A graph of light



Accessories

Index 19.4085.0001.00

Name X-LINE SLIGHT SOUND
ABSORBENT L-572MM RED



Index 19.4085.0002.00

Name X-LINE SLIGHT SOUND
ABSORBENT L-572MM BLUE



Index 19.4085.0003.00

Name X-LINE SLIGHT SOUND
ABSORBENT L-572MM GREY

