

Product: X-LINE SLIGHT L-DOWN LED 2200 MICRO-PRM EDD 24 840 / L-572MM S-1,5M Index: 19.4085.5223.24



Description

Linear luminaire with minimized width. Made of 34 mm wide and 68 mm high aluminum profile. Mounted on slings. Direct light distribution. The optical system is fulfilled by an aperture recessed into the body, facing the end cap. Available opal smooth or microprismatic diffuser made of PMMA. Luminaire in single version. Available colours: anodized aluminum, black (RAL 9005), grey (RAL 9006), white (RAL 9016) or any RAL colour on request. End cap aluminum, painted in the colour of the body. Application of luminaires typically for offices, public spaces, community areas in multi-family buildings. There is the possibility of fitting a luminaire with a sound-absorbing housing.

Product information	Category	/ Surface mounted luminaires
	Family	X-LINE SLIGHT LED
	Name	X-LI <mark>NE SLIG</mark> HT L-DOWN LED 2200 MICRO-PRM EDD 24 840 / L- 572MM S-1,5M
	Index	19.4085.5223.24
		$\overbrace{LED} \textcircled{\mathbb{E}} \textcircled{\mathbb{P}} \textcircled{\mathbb{P}} \textcircled{\mathbb{P}} \textcircled{\mathbb{P}} \textcircled{\mathbb{F}} $

Light and electrical data

Light source	LED
Luminous flux LED [lm]	2395,1
LED power [W]	11,4
Luminaire luminous flux [lm]	1952
Power of luminaire [W]	13,4
Luminaire's light efficiency [lm/W]	145,7
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 86,2° / 111°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	145000
Lx/By	L90/B10
Operating temperature range [°C]	5 ÷ 35
Driver	DIM DALI (EDD)
Power factor $\cos \phi$	>0,95
Circuit load capacity	14 (B10), 24 (B16), 22 (C10), 36 (C16)



Index industry induminum A Image: index index on anodised aluminum Image: index index on anodised aluminum Diffuser Material audininum Diffuser Micro-PRM (micro-Prismatic diffuser PMMA) Image: index index on anodised aluminum Diffuser A graph of light Image: index index on anodised aluminum Image: index index on anodised aluminum Diffuser Accessories Image: index index on anodised aluminum Image: index index on anodised aluminum Image: index index on anodised aluminum Markerial Image: index index on anodised aluminum Markerindit Image: index index ono anodised alu	A Material aluminum Color anodised aluminum Diffusor Micro-PRM (micro-PRM (micro-prismatic diffuser PMMA) Impact resistant IK04 Dimensions [mm] 572 x 34 x 68 A graph of light Impact resistant Impact resistant Impact resistant Impact resistant Impact resistant A graph of light Impact resistant Impact resistant <th>Mechanical data</th> <th></th> <th>Assembly</th> <th>surface mounted on slings</th>	Mechanical data		Assembly	surface mounted on slings
Color anodised aluminum Diffuser Micro-PRM (micro-prismatic diffuser PMMA) Impact resistant IK04 Dimensions [mm] 572 x 34 x 68 A graph of light IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	Color anodised aluminum Diffuser Micro-PRM (micro-prismatic diffuser PMMA) Impact resistant IK04 Dimensions [mm] 572 x 34 x 68 A graph of light A graph of light A graph of light Index 19.4085 0001.00 Name XLINE SLICHT SOUND ASSORBENT L-572MM RED Mare XLINE SLICHT SOUND ASSORBENT L-572MM RED Mare XLINE SLICHT SOUND ASSORBENT L-572MM GREY				
Diffuser Micro-PRM (micro-prismatic diffuser PMMA) Impact resistant IK04 Dimensions [mm] 572 x 34 x 68 A graph of light Iffuser Impact resistant Iffuser A graph of light Iffuser Impact resistant Iffuser Impact resistant Iffuser State Iffuser Impact resistant Iffuser Index 19.4085.001.00 Iffuser Name XLINE SLICHT SOLIDO Name XLINE SLICHT SOLIDO Assorbeent L 572MM RED Iffex 19.4085.001.00 Name XLINE SLICHT SOLIDO Name XLINE SLICHT SOLIDO Assorbeent L 572MM RED Name XLINE SLICHT SOLIDO	Diffuser Micro-PRM (micro-prismatic diffuser PMMA) Impact resistant IK04 Dimensions [mm] 572 x 34 x 68 A graph of light Iffuser Impact resistant Iffuser A graph of light Iffuser Micro-PRM (micro-prismatic diffuser PMMA) Iffuser Dimensions [mm] 572 x 34 x 68 A graph of light Iffuser Micro-PRM (micro-prismatic diffuser PMMA) Iffuser Index 194085.0001.00 Iffuser Name XLINE SLIGHT SOUND ABSORBENT L 572MM RED Iffex 194.085.0002.00 Name XLINE SLIGHT SOUND ABSORBENT L 572MM RED Iffex 194.085.0002.00	Δ			
Impact resistant IK04 Dimensions [mm] 572 x 34 x 68 A graph of light Impact resistant Impact resistant Impact	Impact resistant IK04 Dimensions [mm] 572 x 34 x 68 A graph of light Impact resistant Impact resistant Impact	· · · ·	U		
Dimensions [mm] 572 x 34 x 68 A graph of light Image: state s	Dimensions [mm] 572 x 34 x 68 A graph of light Image: second				
Index 19.4085.0001.00 Name X.LINE SLIGHT SOUND ASSORBENT L.572MM RED	Index 19.4085.0001.00 Name XLINE SLIGHT SOUND ASSORBENT L-572MM RELUE				
Accessories	Accessories	A graph of light			90° 75° 60° 45° 45° 40° 40° 30° 15° 0° 15° 30°
Name X-LINE SLIGHT SOUND ABSORBENT L-572MM RED Name X-LINE SLIGHT SOUND ABSORBENT L-572MM BLUE Name X-LINE SLIGHT SOUND ABSORBENT L-572MM GREY	Name X-LINE SLIGHT SOUND Name X-LINE SLIGHT SOUND ABSORBENT L-572MM RED Name X-LINE SLIGHT SOUND ABSORBENT L-572MM RED Name X-LINE SLIGHT SOUND ABSORBENT L-572MM REU Name X-LINE SLIGHT SOUND ABSORBENT L-572MM REU Name X-LINE SLIGHT SOUND				
Name x-Line slight sound ABSORBENT L-572MM RED Name x-Line slight sound ABSORBENT L-572MM BLUE Name x-Line slight sound ABSORBENT L-572MM GREY	Name X-LINE SLIGHT SOUND Name X-LINE SLIGHT SOUND ABSORBENT L-572MM RED Name X-LINE SLIGHT SOUND ABSORBENT L-572MM GREY	Accessories			
			Index 19,4085,0002,00	Index 19.4085.0	
		Index 19.4085.0001.00 Name X-LINE SLIGHT SOUND	Name X-LINE SLIGHT SOUN	Name X-LINE SI	1003.00 LIGHT SOUND
		Index 19.4085.0001.00 Name X-LINE SLIGHT SOUND ABSORBENT L-572MM RED	Name X-LINE SLIGHT SOUN ABSORBENT L-572MM	Name X-LINE SL BBUE ABSORBE	DO03.00 LIGHT SOUND ENT L-572MM GREY
		Index 19.4085.0001.00 Name X-LINE SLIGHT SOUND ABSORBENT L-572MM RED	Name X-LINE SLIGHT SOUN ABSORBENT L-572MM	Name X-LINE SL BLUE ABSORBE	DO03.00 LIGHT SOUND ENT L-572MM GREY