

4

Product: X-LINE SLIGHT L-DOWN LED 3900 MICRO-PRM E 04 840 / L-1693MM S-1,5M Index: 19.4085.7521.04



Description

Linear luminaire with minimized width. Made of 34 mm wide and 68 mm high aluminum profile. Mounted on slings. Direct light distribution. The optical system is fulfilled by an aperture recessed into the body, facing the end cap. Available opal smooth or microprismatic diffuser made of PMMA. Luminaire in single version. Available colours: anodized aluminum, black (RAL 9005), grey (RAL 9006), white (RAL 9016) or any RAL colour on request. End cap aluminum, painted in the colour of the body. Application of luminaires typically for offices, public spaces, community areas in multi-family buildings.

Product information	Product	inform	ation
---------------------	---------	--------	-------

 Category
 Surface mounted luminaires

 Family
 X-LINE SLIGHT LED

 Name
 X-LINE SLIGHT L-DOWN LED 3900 MICRO-PRM E 04 840 / L-1693MM S-1,5M

ICE

Index 19.4085.7521.04

Light and electrical data

Light source	LED
Luminous flux LED [lm]	4527
LED power [W]	20,7
Luminaire luminous flux [lm]	3689,5
Power of luminaire [W]	23,5
Luminaire's light efficiency [lm/W]	157
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 86,2° / 111°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	80000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor $\cos \phi$	>0,95
Circuit load capacity	12 (B10), 19 (B16), 20 (C10), 32 (C16)



Mechanical data	□tH ⊨= B	Assembly Material Color Diffuser Impact resistant	surface mounted on slings aluminum RAL 9005 (black) Micro-PRM (micro-prismatic diffuser PMMA) IK04
A graph of light		Dimensions [mm]	1693 x 34 x 68
Accessories			
Index 19.4085.0004.00 Name X-LINE SLIGHT SOUND ABSORBENT L-1134MM RED	Index 19.4085.0005.00 Name X-LINE SLIGHT SOUN ABSORBENT L-1134M		GHT SOUND NT L-1134MM GREY