

Product: X-LINE SLIGHT L-DOWN LED 1300 PLX EDD 24 830 / L-572MM S-1,5M Index: 19.4085.1113.24



Description

Linear luminaire with minimized width. Made of 34 mm wide and 68 mm high aluminum profile. Mounted on slings. Direct light distribution. The optical system is fulfilled by an aperture recessed into the body, facing the end cap. Available opal smooth or microprismatic diffuser made of PMMA. Luminaire in single version. Available colours: anodized aluminum, black (RAL 9005), grey (RAL 9006), white (RAL 9016) or any RAL colour on request. End cap aluminum, painted in the colour of the body. Application of luminaires typically for offices, public spaces, community areas in multi-family buildings. There is the possibility of fitting a luminaire with a sound-absorbing housing.

	Category	Surface mounted luminaires
	Family	X-LINE SLIGHT LED
	Name	X-LINE SLIGHT L-DOWN LED 1300 PLX EDD 24 830 / L-572MM S- 1,5M
	Index	19.4085.1113.24
		$\overbrace{LED} \textcircled{\begin{tabular}{ c c c c } \hline \hline$

Light and electrical data

Light source	LED
Luminous flux LED [lm]	1403,7
LED power [W]	6,9
Luminaire luminous flux [lm]	1052,8
Power of luminaire [W]	8,6
Luminaire's light efficiency [lm/W]	122,4
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 99,6° / 103°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	145000
Lx/By	L90/B10
Operating temperature range [°C]	5 ÷ 35
Driver	DIM DALI (EDD)
Power factor $\cos \phi$	>0,95
Circuit load capacity	20 (B10), 31 (B16), 33 (C10), 53 (C16)



Line H Material aluminu	mounted on slings
A Material aluminu A B Color anodise Diffuser PLX (PM) Impact resistant IK04	
A Color anodise Diffuser PLX (PM Impact resistant IK04	
Diffuser PLX (PM Impact resistant IK04	ed aluminum
Impact resistant IK04	
•	init opuly
	1 v 69
	• × 00
A graph of light 10^{10}	
Accessories	
Index 19.4085.0001.00 Index 19.4085.0002.00 Index 19.4085.0003.00	
Name X-LINE SLIGHT SOUND Name X-LINE SLIGHT SOUND Name X-LINE SLIGHT SOUND ABSORBENT L-572MM RED ABSORBENT L-572MM BLUE ABSORBENT L-572MM GREY	