

Product: X-LINE SLIGHT L-DOWN LED 2200 PLX E 24 840 / L-572MM S-1,5M Index: 19.4085.1221.24



Description


Linear luminaire with minimized width. Made of 34 mm wide and 68 mm high aluminum profile. Mounted on slings. Direct light distribution. The optical system is fulfilled by an aperture recessed into the body, facing the end cap. Available opal smooth or microprismatic diffuser made of PMMA. Luminaire in single version. Available colours: anodized aluminum, black (RAL 9005), grey (RAL 9006), white (RAL 9016) or any RAL colour on request. End cap aluminum, painted in the colour of the body. Application of luminaires typically for offices, public spaces, community areas in multi-family buildings. There is the possibility of fitting a luminaire with a sound-absorbing housing.

Product information	Category Surface mounted luminaires		
	Family X-LINE SLIGHT LED		
		ED 2200 PLX E 24 840 / L-572MM S-1,5M	
	Index 19.4085.1221.24	·	
Light and electrical data	Light source	LED	
	Luminous flux LED [lm]	2395,1	
	LED power [W]	11,4	
	Luminaire luminous flux [lm]	1796,3	
	Power of luminaire [W]	13,4	
	Luminaire's light efficiency [lm/W]	134,1	
	Color of the light [K]	4000	
	CRI	>80	
	SDCM (LED sources)	3	
	Beam angle [°]	(C0-C180) / (C90-C270) - 99,6° / 103°	
	Photobiological risk class (IEC/EN 62471)	RG0	
	Protection against electric shock	I	
	Protection degree	IP40	
	Voltage	220240 V, 5060 Hz	
	Lifetime of LED sources [h]	145000	
	Lx/By	L90/B10	
	Operating temperature range [°C]	5 ÷ 35	
	Driver	standard on/off (E)	
	Power factor $\cos \phi$	>0,95	
	Circuit load capacity	46 (B10), 74 (B16), 72 (C10), 115 (C16)	



Mechanical data		Assembly	surface mounted on slings
	∏‡H	Material	aluminum
A	l++ B	Color	anodised aluminum
		Diffuser	PLX (PMMA opal)
		Impact resistant	IK04
		Weight [kg]	1,09
		Dimensions [mm]	572 x 34 x 68
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 45° 45° 45° 45° 45° 45
Accessories			
Index 19.4085.0001.00	Index 19.4085.0002.00	Index 19.40	85.0003.00
Name X-LINE SLIGHT SOUND ABSORBENT L-572MM RED	Name X-LINE SLIGHT SOUND ABSORBENT L-572MM		E SLIGHT SOUND RBENT L-572MM GREY







Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025