

Product: X-LINE SLIGHT L-DOWN LED 4400 PLX EDD 04 830 / L-1134MM S-1,5M Index: 19.4085.2613.04



Description

Category Surface mounted luminaires

Linear luminaire with minimized width. Made of 34 mm wide and 68 mm high aluminum profile. Mounted on slings. Direct light distribution. The optical system is fulfilled by an aperture recessed into the body, facing the end cap. Available opal smooth or microprismatic diffuser made of PMMA. Luminaire in single version. Available colours: anodized aluminum, black (RAL 9005), grey (RAL 9006), white (RAL 9016) or any RAL colour on request. End cap aluminum, painted in the colour of the body. Application of luminaires typically for offices, public spaces, community areas in multi-family buildings. There is the possibility of fitting a luminaire with a sound-absorbing housing.

Product	inform	ation

Light and electrical data

	Family	X-LINE SLIGHT LED			
	Name	me X-LINE SLIGHT L-DOWN LED 4400 PLX EDD 04 830 / L-1134MN 1,5M			
	Index	19.4085.2613.04			
	Light sou	irce	LED		
	Luminou	s flux LED [lm]	4456		
LED power [W]		ver [W]	22,8		
	Luminair	e luminous flux [lm]	3342		
	Power of	luminaire [W]	25,9		
	Luminair	e's light efficiency [lm/W]	129		
	Color of the light [K]		3000		
	CRI		>80		
	SDCM (LED sources)		3		
	Beam an	gle [°]	(C0-C180) / (C90-C270) - 99,6° / 103°		
	Photobiological risk class (IEC/EN 62471) Protection against electric shock Protection degree		RG0		
			I		
			IP40		
	Voltage		220240 V, 5060 Hz		
	Lifetime of	of LED sources [h]	80000		
	Lx/By		L80/B10		
	Operatin	g temperature range [°C]	5 ÷ 35		
	Driver		DIM DALI (EDD)		
	Power fa	ctor cos φ	>0,95		
	Circuit lo	ad capacity	17 (B10), 28 (B16), 26 (C10), 41		

(C16)



Mechanical data		Assembly	surface mounted on slings
	∏‡H	Material	aluminum
A	l+→l B	Color	RAL 9005 (black)
		Diffuser	PLX (PMMA opal)
		Impact resistant	IK04
		Dimensions [mm]	1134 x 34 x 68
A graph of light			105°
			90° 90° 75° 75° 60° 100 60° 45° 200 45° 45° 250 45° 30° 15° 0° 45° 250 50° 45° 250 45° 45° 30°
Accessories			
Index 19.4085.0004.00	Index 19.4085.0005.00	Index 19.4085.00	06.00
Name X-LINE SLIGHT SOUND	Name X-LINE SLIGHT SOUT		
ABSORBENT L-1134MM RED	ABSORBENT L-1134	MM BLUE ABSORBEI	NT L-1134MM GREY