

Product: X-LINE SLIGHT L-DOWN LED 4400 PLX E 24 840 / L-1134MM S-1,5M Index: 19.4085.2621.24



Description

Linear luminaire with minimized width. Made of 34 mm wide and 68 mm high aluminum profile. Mounted on slings. Direct light distribution. The optical system is fulfilled by an aperture recessed into the body, facing the end cap. Available opal smooth or microprismatic diffuser made of PMMA. Luminaire in single version. Available colours: anodized aluminum, black (RAL 9005), grey (RAL 9006), white (RAL 9016) or any RAL colour on request. End cap aluminum, painted in the colour of the body. Application of luminaires typically for offices, public spaces, community areas in multi-family buildings. There is the possibility of fitting a luminaire with a sound-absorbing housing.

	Category	Surface mounted luminaires
	Family	X-LINE SLIGHT LED
	Name	X-LINE SLIGHT L-DOWN LED 4400 PLX E 24 840 / L-1134MM S- 1,5M
	Index	19.4085.2621.24
		$\overbrace{LED} \textcircled{\begin{tabular}{c}{c}{c}{c}{c}{c}{c}{c}{c}{c}{c}{c}{c}$

Light and electrical data

	Light source	LED
	Luminous flux LED [Im]	4790
	LED power [W]	22,8
	Luminaire luminous flux [lm]	3592,5
	Power of luminaire [W]	25,9
	Luminaire's light efficiency [lm/W]	138,7
	Color of the light [K]	4000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 99,6° / 103°
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	145000
	Lx/By	L90/B10
	Operating temperature range [°C]	5 ÷ 35
	Driver	standard on/off (E)
	Power factor $\cos \phi$	>0,95
	Circuit load capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)



Mechanical data Assembly surface mounted on slings A Material aluminum Diffuser PLX (PMMA opal) Impact resistant IKG4 Dimensions (mm) 1134 x 34 x 68 A graph of light Impact resistant IKG4 Dimensions (mm) 1134 x 34 x 68	A Material aluminum Color anodised aluminum Dirensions [mm] 1134 x 34 x 68 A graph of light Impact resistant IKO4 Dirensions [mm] 1134 x 34 x 68 A graph of light Impact resistant Impact resistant A graph of light Impact resistant Impact resistant Impact resistant Impact resistant Impact resistant A graph of light Impact resistant Impact resistant Impact resistant Impact resistant Impact resistant				
A B Color anodised aluminum Diffuser PLX (PMMA opal) Impact resistant IK04 Dimensions (mm) 1134 x 34 x 68 A graph of light Impact resistant If the second of the se	A B Color anodised aluminum Diffuser PLX (PMMA opal) Impact resistant IK04 Dimensions [mm] 1134 x 34 x 68 A graph of light Impact resistant Impact resistant A graph of light Impact resistant Impact resistant Market Resistant Impact resistant Impact resistant Impact resistant Impact resistant Impact resistant A graph of light Impact resistant Impact resistant Impact resistant Impact resistant Impact re	Mechanical data		Assembly	surface mounted on slings
Diffuser PLX (PMMA opal) Impact resistant IK04 Dimensions [mm] 1134 x 34 x 68 A graph of light	Diffuser PLX (PMMA opal) Impact resistant IK04 Dimensions [mm] 1134 x 34 x 68 A graph of light			Material	aluminum
Impact resistant KO4 Dimensions [mm] 1134 x 34 x 68 A graph of light Interview of the second	Impact resistant IK04 Dimensions [mm] 1134 x 34 x 68 A graph of light Impact resistant Impact resistant A graph of light Impact resistant Impact resistant Impact resistant Impact resistant Impact resistant Index 19.4085.0006.00 Impact resistant Impact resistant Index 19.4085.0006.00 Impact resistant Impact resistant ABSORBENT L-1134MM RED Index 19.4085.006.00 Impact resistant resistan	A	B	Color	anodised aluminum
Dimensions [mm] 1134 x 34 x 68 A graph of light Image: space of the space of th	Dimensions [mm] 1134 x 34 x 68 A graph of light Image: state of the state of th			Diffuser	PLX (PMMA opal)
A graph of light http://www.interview.org/action/org/a	A graph of light A graph of light			Impact resistant	IK04
Index 19.4085.0004.00 Index 19.4085.0005.00	Index 19.4085.0004.00 Name XLINE SLIGHT SOUND ASSORBENT L.1134MM RED			Dimensions [mm]	1134 x 34 x 68
Index 19.4085.0004.00 Name X-LINE SLIGHT SOUND ABSORBENT L-1134MM RED Index 19.4085.0005.00 Name X-LINE SLIGHT SOUND ABSORBENT L-1134MM BLUE Index 19.4085.0006.00 Name X-LINE SLIGHT SOUND ABSORBENT L-1134MM GREY	Index 19.4085.0004.00 Index 19.4085.0005.00 Name X-LINE SLIGHT SOUND ABSORBENT L-1134MM RED Name X-LINE SLIGHT SOUND ABSORBENT L-1134MM BLUE ABSORBENT L-1134MM BLUE	A graph of light			90° 75° 60° 45° 200 45° 200 45° 200 45° 200 45° 200 45° 200 45° 200 45° 200 45° 200 45° 200 45° 30°
Name X-LINE SLIGHT SOUND ABSORBENT L-1134MM RED Name X-LINE SLIGHT SOUND ABSORBENT L-1134MM BLUE Name X-LINE SLIGHT SOUND ABSORBENT L-1134MM GREY	Name X-LINE SLIGHT SOUND Name X-LINE SLIGHT SOUND ABSORBENT Name X-LINE SLIGHT SOUND ABSORBENT L-1134MM GREY	Accessories			
ABSORBENT L-1134MM RED ABSORBENT L-1134MM BLUE ABSORBENT L-1134MM GREY	ABSORBENT L-1134MM RED ABSORBENT L-1134MM BLUE ABSORBENT L-1134MM GREY	Index 19.4085.0004.00	Index 19.4085.0005.00	Index 19.4085.000	06.00