

Product: X-LINE SLIM LOW UGR L-DOWN LED 5250 RASTER DAISY-BLACK-WIDE E 24 840 / L-1406MM S-1,5M Index: 19.4088.2821.24



Description

The luminaire is made of aluminum profile. Light distribution in the lower halfspace. Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses an anti-glare louvre. It allows to create lighting systems, facilitating the creation of comfortable vision in the interiors. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	Category Surface mounted luminaires	Category Surface mounted luminaires		
	Family X-LINE SLIM LOW UGR L-DOWN LED			
	Name X-LINE SLIM LOW UGR L-DOWN LED 5250 RAS BLACK-WIDE E 24 840 / L-1406MM S-1,5M	TER DAISY-		
	Index 19.4088.2821.24			
	EAN 5902107242169			
		K ₄ hdoor		
Light and electrical data	Light source LED			
	Luminous flux LED [Im] 5540			
	LED power [W] 28			
	Luminaire luminous flux [lm] 4598,2			
	Power of luminaire [W] 31,8			
	Luminaire's light efficiency [lm/W] 144,6			
	Color of the light [K] 4000			
	CRI >80			
	SDCM (LED sources) 3			
	Beam angle [°] (C0-C180) / (C90-C	C270) - 72,6° / 74,4°		
	Photobiological risk class (IEC/EN RG0 62471)			
	Protection against electric shock			
	Protection degree IP40			
	Voltage 220240 V, 5060	Hz		
	Lifetime of LED sources [h] 100000			
	Lx/By L80/B10			
	Operating temperature range [°C] 5 ÷ 35			
	Driver standard on/off (E	Ξ)		
	Power factor $\cos \varphi$ >0,95			
	Circuit load capacity 19 (B10), 30 (B16) (C16)	, 31 (C10), 50		



Mechanical data	⊟H B	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum anodised aluminum RASTER (anti-glare louver) IK04 2,38 1406 x 48 x 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 45° 45° 45° 45




Accessories


Index 6E1-500KWANK-3 Name SUSPENSION NEW TYPE-A+B 24



- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB24K-3
 - Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 3X SET

