

Product: X-LINE SLIM LOW UGR L-DOWN LED 5250 RASTER DAISY-BLACK-WIDE E 21 840 / L-1406MM S-1,5M

Index: 19.4088.2821.21



Description

The luminaire is made of aluminum profile. Light distribution in the lower half-space. Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses an anti-glare louvre. It allows to create lighting systems, facilitating the creation of comfortable vision in the interiors. The X-Line Slim luminaire is designed for mounting on suspensions. *Selected luminary variants are available with ENEC certificate.

Product information

Category	Surface mounted luminaires
Family	X-LINE SLIM LOW UGR L-DOWN LED
Name	X-LINE SLIM LOW UGR L-DOWN LED 5250 RASTER DAISY-BLACK-WIDE E 21 840 / L-1406MM S-1,5M
Index	19.4088.2821.21
EAN	5902107554972



Light and electrical data


Light source	LED
Luminous flux LED [lm]	5540
LED power [W]	28
Luminaire luminous flux [lm]	4598,2
Power of luminaire [W]	31,8
Luminaire's light efficiency [lm/W]	144,6
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 72,6° / 74,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	16 (B10), 26 (B16), 23 (C10), 37 (C16)

Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9006 (grey)
Diffuser	RASTER (anti-glare louver)
Impact resistant	IK04
Dimensions [mm]	1406 x 48 x 70

A graph of light



Accessories

Index 6E1-500KWANK-3

Name SUSPENSION NEW TYPE-A+B 24
LENGHT 1,5M WIRE 3X SET



Index 6E1-8670-B-1,5-3X

Name SUSPENSION NEW TYPE-F
LENGHT-1,5 METER WIRE 3X 1-
POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E
LENGHT-1,5 METER WITHOUT
WIRE 1-POINT



Index 19.3272.0704.24

Name SUSPENSION NEW TYPE-A+E 24
LENGHT 1,5M WIRE 3X SET



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D
LENGHT-1,5 METER WIRE 3X 1-
POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C
LENGHT-1,5 METER WITHOUT
WIRE 1-POINT

