

Product: X-LINE SLIM LOW UGR L-DOWN LED 5250 RASTER DAISY-BLACK-WIDE EDD 24 840 / L-1406MM S-1,5M Index: 19.4088.2823.24



## Description

The luminaire is made of aluminum profile. Light distribution in the lower halfspace. Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses an anti-glare louvre. It allows to create lighting systems, facilitating the creation of comfortable vision in the interiors. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	Category Su	urface mounted luminaires	
	Family X-I	LINE SLIM LOW UGR L-DOWN LED	
		NameX-LINE SLIM LOW UGR L-DOWN LED 5250 RASTER DAISY- BLACK-WIDE EDD 24 840 / L-1406MM S-1,5M	
	Index 19	9.4088.2823.24	
	EAN 59	902107242190	
		$\overbrace{ED} \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus_{1 \neq 0} \bigoplus_{1 \neq 0} \bigoplus \bigoplus_{1 \neq 0} \bigoplus_{1 \neq$	
Light and electrical data	Light source	LED	
	Luminous flux	ux LED [lm] 5540	
	LED power [V	W] 28	
	Luminaire lur	minous flux [lm] 4598,2	
	Power of lum	ninaire [W] <b>31,8</b>	
	Luminaire's li	light efficiency [Im/W] 144,6	
	Color of the li	light [K] 4000	
	CRI	>80	
	SDCM (LED S	sources) 3	
	Beam angle [	[°] (C0-C180) / (C90-C270) - 72,6° / 74,4"	
	Photobiologic 62471)	cal risk class (IEC/EN RG0	
	Protection ag	gainst electric shock I	
	Protection de	egree IP40	
	Voltage	220240 V, 5060 Hz	
	Lifetime of LE	ED sources [h] <b>100000</b>	
	Lx/By	L80/B10	
	Operating ter	mperature range [°C] 5 ÷ 35	
	Driver	DIM DALI (EDD)	
	Power factor	r cos φ >0,95	
	Circuit load c	capacity 17 (B10), 28 (B16), 26 (C10), 41 (C16)	



Mechanical data	∏tH ⊨≓ B	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum anodised aluminum RASTER (anti-glare louver) IK04 2,56 1406 x 48 x 70
A graph of light			105°       105°         90°       90°         75°       90°         60°       320         45°       60°         45°       480         45°       480         45°       90°         10°       90°         90°       90°         90°       90°         90°       90°         90°       90°         60°       320         45°       90°         45°       90°         90°       15°         90°       15°         90°       15°         90°       15°         90°       15°         90°       15°         90°       15°         90°       15°         90°       15°         90°       15°         90°       15°



## Accessories

Index 6E1-500KWANK-5 Name SUSPENSION NEW TYPE-A+B 24



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



Index 6E1-8670-B-1,5-5X
Name SUSPENSION NEW TYPE-F
LENGHT-1,5 METER WIRE 5X 1POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.3272.1205.00

- Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 6E1-500KWB24K-5

Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 5X SET



