

**Product:** X-LINE SLIM LOW UGR L-DOWN LED 8400 RASTER DAISY-BLACK-WIDE E 04 830 / L-2248MM S-1,5M

**Index:** 19.4088.3411.04



## Description

The luminaire is made of aluminum profile. Light distribution in the lower half-space. Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses an anti-glare louvre. It allows to create lighting systems, facilitating the creation of comfortable vision in the interiors. The X-Line Slim luminaire is designed for mounting on suspensions.

## Product information


Category	Surface mounted luminaires
Family	X-LINE SLIM LOW UGR L-DOWN LED
Name	X-LINE SLIM LOW UGR L-DOWN LED 8400 RASTER DAISY-BLACK-WIDE E 04 830 / L-2248MM S-1,5M
Index	19.4088.3411.04



## Light and electrical data


Light source	LED
Luminous flux LED [lm]	8424
LED power [W]	44,8
Luminaire luminous flux [lm]	6991,9
Power of luminaire [W]	50,9
Luminaire's light efficiency [lm/W]	137,4
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 72,6° / 74,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	12 (B10), 19 (B16), 20 (C10), 32 (C16)

**Mechanical data**



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9005 (black)
Diffuser	RASTER (anti-glare louvre)
Impact resistant	IK04
Dimensions [mm]	2248 x 48 x 70

**A graph of light**



## Accessories

Index 6E1-500KW04K-3

Name SUSPENSION NEW TYPE-A+B 04  
LENGHT 1,5M WIRE 3X SET



Index 6E1-8670-B-1,5-3X

Name SUSPENSION NEW TYPE-F  
LENGHT-1,5 METER WIRE 3X 1-  
POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E  
LENGHT-1,5 METER WITHOUT  
WIRE 1-POINT



Index 6E1-500KWB04K-3

Name SUSPENSION NEW TYPE-A+E 04  
LENGHT 1,5M WIRE 3X SET



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D  
LENGHT-1,5 METER WIRE 3X 1-  
POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C  
LENGHT-1,5 METER WITHOUT  
WIRE 1-POINT

