

Product: X-LINE SLIM L-DOWN LED 3900 MICRO-PRM E 04 830 / L-1698MM S-1,5M

Index: 19.4089.5511.04



## **Description**

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

### **Product information**

Category	Surface mounted luminaires
Family	X-LINE SLIM LED
Name	X-LINE SLIM L-DOWN LED 3900 MICRO-PRM E 04 830 / L-1698MM S-1,5M $$
Index	19.4089.5511.04
EAN	5902107426507















## Light and electrical data


Light source	LED
Luminous flux LED [lm]	3807
LED power [W]	18,6
Luminaire luminous flux [lm]	2817,2
Power of luminaire [W]	21,1
Luminaire's light efficiency [lm/W]	133,5
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	000 0401/ 50 0011
voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
	,
Lifetime of LED sources [h]	100000
Lifetime of LED sources [h] Lx/By	100000 L80/B10
Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	100000 L80/B10 5 ÷ 35



Mechanical data		Assembly	surface mounted on slings
	□tH B	Material	aluminum
Α		Color	RAL 9005 (black)
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Weight [kg]	3

Dimensions [mm]

# A graph of light



1698 x 48 x 70







### **Accessories**

Index 6E1-500KW04K-3

Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 3X SET



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Index 6E1-8670-B-1,5-3X

Name SUSPENSION NEW TYPE-F LENGHT-1,5 METER WIRE 3X 1-POINT




Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-500KWB04K-3

Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 3X SET

