


## Product: X-LINE SLIM L-DOWN LED 3900 MICRO-PRM E 24 840 / L-1698MM S-1,5M Index: 19.4089.5521.24



## Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	Category Surface mounted luminaires		
	Family X-LINE SLIM LED		
	Name X-LINE SLIM L-DOWN LED 3900 MICRO-PRM E 24 840 / L-1698MM S-1,5M		
	Index 19.4089.5521.24		
	EAN 5902107220839		
	$\begin{array}{c} \hline \\ \hline $		
Light and electrical data	Light source LED		
3	Luminous flux LED [lm] 4008		
	LED power [W] 18,6		
	Luminaire luminous flux [Im] 2965,9		
	Power of luminaire [W] 21,1		
	Luminaire's light efficiency [lm/W] 140,6		
	Color of the light [K] 4000		
	CRI >80		
	SDCM (LED sources) 3		
	Beam angle [°] (C0-C180) / (C90-C270) - 88,4° / 86°		
	Photobiological risk class (IEC/EN RG0 62471)		
	Protection against electric shock I		
	Protection degree IP40		
	Voltage 220240 V, 5060 Hz		
	Lifetime of LED sources [h] 100000		
	Lx/By <b>L80/B10</b>		
	Operating temperature range [°C] 5 ÷ 35		
	Driver standard on/off (E)		
	Power factor $\cos \varphi$ >0,95		
	Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16)		



Mechanical data	⊟tH t	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum anodised aluminum Micro-PRM (micro-prismatic diffuser PMMA) IK04 2,82 1698 x 48 x 70
A graph of light			90° 75° 60° 45° 300 30° 15° 0° 45° 45° 45° 45° 45° 45° 45° 45° 45° 45




## Accessories


Index 6E1-500KWANK-3 Name SUSPENSION NEW TYPE-A+B 24



- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB24K-3
  - Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 3X SET

