


Product: X-LINE SLIM L-DOWN LED 3900 MICRO-PRM E 34 840 / L-1698MM S-1,5M Index: 19.4089.5521.34



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information		Category Surface mounted luminaires			
		Family	-		
		Name	X-LINE SLIM L-DOWN LED 3900 MICRO-PRM E 34 840 / L-1698MM S-1,5M		
		Index 19.4089.5521.34			
		EAN	5902107414061		
			$\begin{array}{c} \hline \\ \hline $		
Light and electrical data		Light sou	ource LED		
		Luminou	bus flux LED [lm] 4008		
		LED pow	ower [W] 18,6		
		Luminair	aire luminous flux [Im] 2965,9		
		Power of	of luminaire [W] 21,1		
		Luminair	aire's light efficiency [lm/W] 140,6		
		Color of t	of the light [K] 4000		
		CRI	>80		
		SDCM (L	(LED sources) 3		
		Beam an	angle [°] (C0-C180) / (C90-C270) - 88,4° / 86°		
		Photobio 62471)	iological risk class (IEC/EN RG0		
		Protectio	ion against electric shock I		
		Protectio	ion degree IP40		
		Voltage	220240 V, 5060 Hz		
		Lifetime	e of LED sources [h] 100000		
		Lx/By	L80/B10		
		Operatin	ing temperature range [°C] 5 ÷ 35		
		Driver	standard on/off (E)		
		Power fa	factor cos φ >0,95		
		Circuit lo	load capacity 25 (B10), 40 (B16), 39 (C10), 62 (C16)		




Mechanical data	∏tH ⊌	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum RAL 9016 (white) Micro-PRM (micro-prismatic diffuser PMMA) IK04 2,93 1698 x 48 x 70
A graph of light			$\int_{0}^{105^{\circ}} \int_{0}^{105^{\circ}} \int_{0}^{105^{$




Accessories


- Index 6E1-500KW34K-3
- Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 3X SET




- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB34K-3
- Name SUSPENSION NEW TYPE-A+E 34 LENGHT 1,5M WIRE 3X SET



