


Product: X-LINE SLIM L-DOWN LED 6600 MICRO-PRM E 04 830 / L-1698MM S-1,5M Index: 19.4089.5811.04



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	Category Surface mounted luminaires
	Family X-LINE SLIM LED
	Name X-LINE SLIM L-DOWN LED 6600 MICRO-PRM E 04 830 / L-1698MM S-1,5M
	Index 19.4089.5811.04
	EAN 5902107333157
	$\overbrace{LED} \textcircled{\begin{tabular}{ c c c c } \hline \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ $
Light and electrical data	Light source LED
	Luminous flux LED [Im] 6663
	LED power [W] 32,7
	Luminaire luminous flux [lm] 4930,6
	Power of luminaire [W] 37,2
	Luminaire's light efficiency [Im/W] 132,5
	Color of the light [K] 3000
	CRI >80
	SDCM (LED sources) 3
	Beam angle [°] (C0-C180) / (C90-C270) - 88,4° / 86°
	Photobiological risk class (IEC/EN RG0 62471)
	Protection against electric shock
	Protection degree IP40
	Voltage 220240 V, 5060 Hz
	Lifetime of LED sources [h] 100000
	Lx/By L80/B10
	Operating temperature range [°C] 5 ÷ 35
	Driver standard on/off (E)
	Power factor $\cos \varphi$ >0,95
	Circuit load capacity 25 (B10), 40 (B16), 39 (C10), 62 (C16)



Mechanical data	□tH ⊌ B	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) Micro-PRM (micro-prismatic diffuser PMMA) IK04 2,96 1698 x 48 x 70
A graph of light			$l_{10}^{10} \\ l_{10}^{10} \\ l$




Accessories


- Index 6E1-500KW04K-3
- Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 3X SET



- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT









- Index 19.3272.1205.00
- Name SUSPENSION NEW TYPE-E
- LENGHT-1,5 METER WITHOUT WIRE 1-POINT



- Index 6E1-500KWB04K-3
- Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 3X SET

