

## Product: X-LINE SLIM L-DOWN LED 8800 MICRO-PRM EDD 34 840 / L-2258MM S-1,5M Index: 19.4089.6923.34



## Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	Category Surface mounted luminaires		
	Family X-LINE SLIM LED		
	Name X-LINE SLIM L-DOWN LED 8800 MICRO-PRM EDD 34 840 / L- 2258MM S-1,5M		
	Index 19.4089.6923.34		
	EAN <b>5902107554064</b>		
	$\overbrace{LED} \textcircled{\ } \fbox{\ } \textcircled{\ } \swarrow{\ } $		
Light and electrical data	Light source LED		
	Luminous flux LED [Im] 9352		
	LED power [W] <b>43,6</b>		
	Luminaire luminous flux [lm] 6920,5		
	Power of luminaire [W] 49,5		
	Luminaire's light efficiency [Im/W] 139,8		
	Color of the light [K] 4000		
	CRI >80		
	SDCM (LED sources) 3		
	Beam angle [°] (C0-C180) / (C90-C270) - 88,4° / 86°		
	Photobiological risk class (IEC/EN <b>RG0</b> 62471)		
	Protection against electric shock		
	Protection degree IP40		
	Voltage 220240 V, 5060 Hz		
	Lifetime of LED sources [h] 100000		
	Lx/By <b>L80/B10</b>		
	Operating temperature range [°C] 5 ÷ 35		
	Driver DIM DALI (EDD)		
	Power factor $\cos \varphi$ >0,95		
	Circuit load capacity 14 (B10), 23 (B16), 22 (C10), 35 (C16)		



Mechanical data		Assembly	surface mounted on slings
	[]‡н	Material	aluminum
Α	l++  B	Color	RAL 9016 (white)
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	2258 x 48 x 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 45° 40° 45° 40° 45° 45° 45° 45° 45° 45° 45° 45° 45° 45





## Accessories


- Index 6E1-500KW34K-5
- Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 5X SET



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB24K-5
- Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 5X SET

