

Product: X-LINE SLIM L-DOWN LED 2600 PLX E 24 840 / L-1138MM S-1,5M

Index: 19.4089.1321.24



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions. There is the possibility of fitting a luminaire with a sound-absorbing housing.

Product information

Category	Surface mounted luminaires
Family	X-LINE SLIM LED
Name	X-LINE SLIM L-DOWN LED 2600 PLX E 24 840 / L-1138MM S-1,5M
Index	19.4089.1321.24
EAN	5902107220747















Light and electrical data


Light source	LED	
Luminous flux LED [lm]	2672	
LED power [W]	12,4	
Luminaire luminous flux [lm]	1710,1	
Power of luminaire [W]	14,1	
Luminaire's light efficiency [lm/W]	121,3	
Color of the light [K]	4000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP40	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000	
Lx/By	L80/B10	
Operating temperature range [°C]	5 ÷ 35	
Driver	standard on/off (E)	
Power factor cos φ	>0,95	
Circuit load capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)	



Mechanical data	Ass	sembly	surface mounted on slings
] Ма	aterial	aluminum
A B	Col	blor	anodised aluminum
	Diff	ffuser	PLX (PMMA opal)
	Imp	pact resistant	IK04
	We	eight [kg]	2

Dimensions [mm]

A graph of light



1138 x 48 x 70







Accessories

Index 6E1-500KWANK-3

Name SUSPENSION NEW TYPE-A+B 24 LENGHT 1,5M WIRE 3X SET




Index 6E1-8670-B-1,5-3X

Name SUSPENSION NEW TYPE-F LENGHT-1,5 METER WIRE 3X 1-




Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.4089.0004.00

Name X-LINE SLIM SOUND
ABSORBENT L-1138MM RED



Index 6E1-500KWB24K-3

Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 3X SET



Index 19.4089.0005.00

Name X-LINE SLIM SOUND
ABSORBENT L-1138MM BLUE



Index 19.4089.0006.00

Index 6E1-9875-4-1,5-3X

POINT

Name SUSPENSION NEW TYPE-D

LENGHT-1,5 METER WIRE 3X 1-

Name X-LINE SLIM SOUND
ABSORBENT L-1138MM GREY

