


Product: X-LINE SLIM L-DOWN LED 3900 PLX EDD 34 830 / L-1698MM S-1,5M Index: 19.4089.2513.34



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

| Product information | Category Surface mounted luminaires | | |
|---------------------------|---|--|--|
| | Family X-LINE SLIM LED | | |
| | Name X-LINE SLIM L-DOWN LED 3900 PLX EDD 34 830 / L-1698MM S- 1,5M | | |
| | Index 19.4089.2513.34 | | |
| | EAN 5902107551322 | | |
| | $\overbrace{LED} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \end{array}{\end{array}}$ | | |
| Light and electrical data | Light source LED | | |
| | Luminous flux LED [Im] 3807 | | |
| | LED power [W] 18,6 | | |
| | Luminaire luminous flux [Im] 2436,5 | | |
| | Power of luminaire [W] 21,1 | | |
| | Luminaire's light efficiency [lm/W] 115,5 | | |
| | Color of the light [K] 3000 | | |
| | CRI >80 | | |
| | SDCM (LED sources) 3 | | |
| | Beam angle [°] (C0-C180) / (C90-C270) - 96,4° / 90,2 | | |
| | Photobiological risk class (IEC/EN RG0 62471) | | |
| | Protection against electric shock | | |
| | Protection degree IP40 | | |
| | Voltage 220240 V, 5060 Hz | | |
| | Lifetime of LED sources [h] 100000 | | |
| | Lx/By L80/B10 | | |
| | Operating temperature range [°C] 5 ÷ 35 | | |
| | Driver DIM DALI (EDD) | | |
| | Power factor $\cos \phi$ >0,95 | | |
| | Circuit load capacity 17 (B10), 28 (B16), 26 (C10), 41 (C16) | | |



| Mechanical data | ∏tH B | Assembly Material Color Diffuser Impact resistant Dimensions [mm] | surface mounted on slings aluminum RAL 9016 (white) PLX (PMMA opal) IK04 1698 x 48 x 70 |
|------------------|----------|--|--|
| A graph of light | | | 105 90 90 90 90 90 90 90 90 90 90 |
| | | | |





Accessories


- Index 6E1-500KW34K-5
- Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 5X SET



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB24K-5
- Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 5X SET

