

## Product: X-LINE SLIM L-DOWN LED 6600 PLX E 04 830 / L-1698MM S-1,5M Index: 19.4089.2811.04



## Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product	inform	ation

Categor	y Surface mounted luminaires
Family	X-LINE SLIM LED
Name	X-LINE SLIM L-DOWN LED 6600 PLX E 04 830 / L-1698MM S-1,5M
Index	19.4089.2811.04
EAN	5902107361624
	$\overbrace{E} \bigoplus \overbrace{E} \bigoplus \overbrace{P} \bigcap \bigl{P} \bigcap \bigl{P} \bigcap I I I I I I I I I I I I I I I I I I$

## Light and electrical data

Light source	LED
Luminous flux LED [Im]	6663
LED power [W]	32,7
Luminaire luminous flux [lm]	4264,3
Power of luminaire [W]	37,2
Luminaire's light efficiency [lm/W]	114,6
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)



Mechanical data	∏H B	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) PLX (PMMA opal) IK04 2,9 1698 x 48 x 70
A graph of light			$\int_{0}^{10^{\circ}} \int_{0}^{0} \int_{0}^{0}$




## Accessories


- Index 6E1-500KW04K-3
- Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 3X SET



- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT









- Index 19.3272.1205.00
- Name SUSPENSION NEW TYPE-E
- LENGHT-1,5 METER WITHOUT WIRE 1-POINT



- Index 6E1-500KWB04K-3
- Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 3X SET

