

Product: X-LINE SLIM L-DOWN LED 6600 PLX E 34 840 / L-1698MM S-1,5M Index: 19.4089.2821.34



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product Information	Product inform	nation
---------------------	----------------	--------

	Category	gory Surface mounted luminaires					
FamilyX-LINE SLIM LEDNameX-LINE SLIM L-DOWN LED 6600 PLX E 34 840 / L-1698MM S-1,							
							Index
	EAN	5902107553418					
		$(\mathbf{E}) \bigoplus_{LED} (\mathbf{E}) \bigoplus_{P_{A}} (\mathbf{P}_{A}) \bigoplus_{I \in A} (\mathbf{E}) (\mathbf{E})$					

Light and electrical data

Light source	LED
Luminous flux LED [Im]	7014
LED power [W]	32,7
Luminaire luminous flux [lm]	4489
Power of luminaire [W]	37,2
Luminaire's light efficiency [lm/W]	120,7
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)




Mechanical data	∏tH B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9016 (white) PLX (PMMA opal) IK04 1698 x 48 x 70
A graph of light			105 90 90 90 90 75 60 60 100 150 45 90 100 100 150 150 150 150 150 15




Accessories

- Index 6E1-500KW34K-3
- Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 3X SET




- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB34K-3
- Name SUSPENSION NEW TYPE-A+E 34 LENGHT 1,5M WIRE 3X SET



