


## Product: X-LINE SLIM L-DOWN LED 6600 PLX EDD 24 840 / L-1698MM S-1,5M Index: 19.4089.2823.24



## Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	Category Surface mounted luminaires			
	Family X-LINE SLIM LED			
	Name X-LINE SLIM L-DOWN LED 6600 PLX EDD 24 840 / L-1698MM S- 1,5M			
	Index 19.4089.2823.24			
	EAN <b>5902107220884</b>			
	$\begin{array}{c} \hline \\ \hline $			
Light and electrical data	Light source LED			
	Luminous flux LED [Im] 7014			
	LED power [W] 32,7			
	Luminaire luminous flux [lm] 4489			
	Power of luminaire [W] 37,2			
	Luminaire's light efficiency [lm/W] 120,7			
	Color of the light [K] 4000			
	CRI >80			
	SDCM (LED sources) 3			
	Beam angle [°] (C0-C180) / (C90-C270) - 96,4° / 90,			
	Photobiological risk class (IEC/EN RG0 62471)			
	Protection against electric shock I			
	Protection degree IP40			
	Voltage 220240 V, 5060 Hz			
	Lifetime of LED sources [h] 100000			
	Lx/By <b>L80/B10</b>			
	Operating temperature range [°C] 5 ÷ 35			
	Driver DIM DALI (EDD)			
	Power factor cos φ >0,95			
	Circuit load capacity 14 (B10), 23 (B16), 22 (C10), 35 (C16)			



Mechanical data	∏tH B	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum anodised aluminum PLX (PMMA opal) IK04 2,9 1698 x 48 x 70
A graph of light			$l_{10}^{10} \\ f_{10}^{0} \\ f_{$



## Accessories

Index 6E1-500KWANK-5 Name SUSPENSION NEW TYPE-A+B 24



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



Index 6E1-8670-B-1,5-5X
Name SUSPENSION NEW TYPE-F
LENGHT-1,5 METER WIRE 5X 1POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.3272.1205.00

- Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 6E1-500KWB24K-5

Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 5X SET



