


## Product: X-LINE SLIM L-DOWN LED 6600 PLX EDD 21 840 / L-1698MM S-1,5M Index: 19.4089.2823.21



## Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	Category Surface mounted luminaires
	Family X-LINE SLIM LED
	Name X-LINE SLIM L-DOWN LED 6600 PLX EDD 21 840 / L-1698MM S- 1,5M
	Index 19.4089.2823.21
	EAN <b>5902107553517</b>
	$\overbrace{LED} \textcircled{} \end{array}$
Light and electrical data	Light source LED
	Luminous flux LED [Im] 7014
	LED power [W] 32,7
	Luminaire luminous flux [lm] 4489
	Power of luminaire [W] 37,2
	Luminaire's light efficiency [lm/W] 120,7
	Color of the light [K] 4000
	CRI >80
	SDCM (LED sources) 3
	Beam angle [°] (C0-C180) / (C90-C270) - 96,4° / 90,2°
	Photobiological risk class (IEC/EN <b>RG0</b> 62471)
	Protection against electric shock I
	Protection degree IP40
	Voltage 220240 V, 5060 Hz
	Lifetime of LED sources [h] 100000
	Lx/By <b>L80/B10</b>
	Operating temperature range [°C] 5 ÷ 35
	Driver DIM DALI (EDD)
	Power factor $\cos \phi$ >0,95
	Circuit load capacity <b>17 (B10), 28 (B16), 26 (C10), 41</b> (C16)



Mechanical data	⊟‡H B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9006 (grey) PLX (PMMA opal) IK04 1698 x 48 x 70
A graph of light			$\int_{0}^{105^{\circ}} \int_{0}^{10^{\circ}} \int_{$



## Accessories

Index 6E1-500KWANK-5 Name SUSPENSION NEW TYPE-A+B 24



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



Index 6E1-8670-B-1,5-5X
Name SUSPENSION NEW TYPE-F
LENGHT-1,5 METER WIRE 5X 1POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.3272.1205.00

- Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 6E1-500KWB24K-5

Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 5X SET



