


## Product: X-LINE SLIM L-DOWN LED 6600 PLX EDD 34 840 / L-1698MM S-1,5M Index: 19.4089.2823.34



## Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information		Category Surface mounted luminaires			
		nily X-LINE SLIM LED			
		me X-LINE SLIM L-DOWN LED 6600 1,5M	) PLX EDD 34 840 / L-1698MM S-		
		ex 19.4089.2823.34			
		<b>5902107251857</b>			
Light and electrical data		nt source	ED		
		ninous flux LED [lm] 7	014		
		power [W] 3	2,7		
		ninaire luminous flux [lm] 4	489		
		ver of luminaire [W] 3	7,2		
		ninaire's light efficiency [lm/W] 1	20,7		
		or of the light [K] 4	000		
		>	80		
		CM (LED sources) 3			
		Im angle [°]	C0-C180) / (C90-C270) - 96,4° / 90,2°		
		tobiological risk class (IEC/EN R 71)	2G0		
		tection against electric shock			
		tection degree	240		
		age 2	20240 V, 5060 Hz		
		time of LED sources [h] 1	00000		
		By L	80/B10		
		erating temperature range [°C] 5	÷ 35		
		ver D	IM DALI (EDD)		
		ver factor $\cos \varphi$ >	0,95		
			7 (B10), 28 (B16), 26 (C10), 41 C16)		



Mechanical data	∏tH ⊩H B	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum RAL 9016 (white) PLX (PMMA opal) IK04 2,9 1698 x 48 x 70
A graph of light			$\frac{105^{\circ}}{90^{\circ}}$





## Accessories


- Index 6E1-500KW34K-5
- Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 5X SET



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB24K-5
- Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 5X SET

