


Product: X-LINE SLIM L-DOWN LED 5200 PLX E 24 830 / L-2258MM S-1,5M Index: 19.4089.3711.24



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

| Product information |
|---------------------|
|---------------------|

| | Category | Surface mounted luminaires |
|--|----------|--|
| | Family | X-LINE SLIM LED |
| | Name | X-LINE SLIM L-DOWN LED 5200 PLX E 24 830 / L-2258MM S-1,5M |
| | Index | 19.4089.3711.24 |
| | EAN | 5902107552602 |
| | | $ (\mathbf{E}) $ |

Light and electrical data

| Light source | LED |
|---|---|
| Luminous flux LED [lm] | 5076 |
| LED power [W] | 24,8 |
| Luminaire luminous flux [lm] | 3248,6 |
| Power of luminaire [W] | 28,2 |
| Luminaire's light efficiency [lm/W] | 115,2 |
| Color of the light [K] | 3000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 96,4° / 90,2° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP40 |
| Voltage | 220240 V, 5060 Hz |
| Lifetime of LED sources [h] | 100000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 35 |
| Driver | standard on/off (E) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 25 (B10), 40 (B16), 39 (C10), 62 (C16) |



| Mechanical data | ⊟‡H B | Assembly Material Color Diffuser Impact resistant Dimensions [mm] | surface mounted on slings aluminum anodised aluminum PLX (PMMA opal) IK04 2258 x 48 x 70 |
|------------------|----------|--|---|
| A graph of light | | | 105° 90° 90° 75° 60° 45° 45° 45° 45° 45° 45° 45° 45 |
| | | | |




Accessories


Index 6E1-500KWANK-3 Name SUSPENSION NEW TYPE-A+B 24



- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB24K-3
 - Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 3X SET

