

## Product: X-LINE SLIM L-DOWN LED 5200 PLX E 34 830 / L-2258MM S-1,5M Index: 19.4089.3711.34



## Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

(C16)

Product information	Category Surface mounted luminaires	
	Family X-LINE SLIM LED	
	Name X-LINE SLIM L-DOWN LED 5200 PLX B	E 34 830 / L-2258MM S-1,5M
	Index 19.4089.3711.34	
Light and electrical data	Light source LED	
	Luminous flux LED [lm] 5076	
	LED power [W] 24,8	
	Luminaire luminous flux [lm] 3248,6	
	Power of luminaire [W] 28,2	
	Luminaire's light efficiency [lm/W] 115,2	
	Color of the light [K] <b>3000</b>	
	CRI >80	
	SDCM (LED sources) 3	
	Beam angle [°] (C0-C18	0) / (C90-C270) - 96,4° / 90,2°
	Photobiological risk class (IEC/EN <b>RG0</b> 62471)	
	Protection against electric shock	
	Protection degree IP40	
	Voltage <b>220240</b>	V, 5060 Hz
	Lifetime of LED sources [h] 100000	
	Lx/By <b>L80/B10</b>	
	Operating temperature range [°C] 5 ÷ 35	
	Driver standar	d on/off (E)
	Power factor $\cos \phi$ >0,95	
	Circuit load capacity 25 (B10)	, 40 (B16), 39 (C10), 62




Mechanical data	∏tH ⊨+T B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slingsaluminumRAL 9016 (white)PLX (PMMA opal)IK042258 x 48 x 70
A graph of light			$105^{\circ}$



## Accessories


- Index 6E1-500KW34K-3
- Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 3X SET



- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT








LENGHT-1,5 METER WITHOUT WIRE 1-POINT



- Index 19.3272.1205.00
- Name SUSPENSION NEW TYPE-E
- LENGHT-1,5 METER WITHOUT WIRE 1-POINT



- Index 6E1-500KWB34K-3
- Name SUSPENSION NEW TYPE-A+E 34 LENGHT 1,5M WIRE 3X SET



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 18-06-2025