

Product: X-LINE SLIM L-DOWN LED 8800 PLX EDD 04 840 / L-2258MM S-1,5M

Index: 19.4089.3923.04



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information

Category	Surface mounted luminaires
Family	X-LINE SLIM LED
Name	X-LINE SLIM L-DOWN LED 8800 PLX EDD 04 840 / L-2258MM S- 1,5M
Index	19.4089.3923.04
EAN	5902107303204















Light and electrical data

Light source	LED
Luminous flux LED [lm]	9352
LED power [W]	43,6
Luminaire luminous flux [lm]	5985,3
Power of luminaire [W]	49,5
Luminaire's light efficiency [lm/W]	120,9
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Protection degree Voltage	IP40 220240 V, 5060 Hz
Voltage	220240 V, 5060 Hz
Voltage Lifetime of LED sources [h]	220240 V, 5060 Hz 100000
Voltage Lifetime of LED sources [h] Lx/By	220240 V, 5060 Hz 100000 L80/B10
Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	220240 V, 5060 Hz 100000 L80/B10 5 ÷ 35




ľ	Mechanical	data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9005 (black)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	4,5
Dimensions [mm]	2258 x 48 x 70

A graph of light







Accessories

Index 6E1-500KW04K-5

Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 5X SET



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT




Index 6E1-8670-B-1,5-5X

Name SUSPENSION NEW TYPE-F LENGHT-1,5 METER WIRE 5X 1-POINT




Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-500KWB04K-5

Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 5X SET

