


Product: X-LINE SLIM L-DOWN LED 3250 OPTICS-ASYM E 34 830 / L-1425MM S-1,5M Index: 19.4090.4411.34



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	Category Surface mounted luminaires	
	Family X-LINE SLIM LED	
	Name X-LINE SLIM L-DOWN LED 3250 OPTICS-ASYM E 34 830 / L- 1425MM S-1,5M	
	Index 19.4090.4411.34	
	EAN 5902107550998	
	$\overbrace{ED} \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus_{ndoor} \bigoplus_$	
Light and electrical data	Light source LED	
	Luminous flux LED [Im] 3172,5	
	LED power [W] 15,5	
	Luminaire luminous flux [lm] 2506,3	
	Power of luminaire [W] 17,6	
	Luminaire's light efficiency [lm/W] 142,4	
	Color of the light [K] 3000	
	CRI >80	
	SDCM (LED sources) 3	
	Beam angle [°] asymmetric light distribution - Imax=-20°	
	Photobiological risk class (IEC/EN RG0 62471)	
	Protection against electric shock	
	Protection degree IP40	
	Voltage 220240 V, 5060 Hz	
	Lifetime of LED sources [h] 100000	
	Lx/By L80/B10	
	Operating temperature range [°C] 5 ÷ 35	
	Driver standard on/off (E)	
	Power factor $\cos \varphi$ >0,95	
	Circuit load capacity 25 (B10), 40 (B16), 39 (C10), 62 (C16)	




Mechanical data		Assembly	surface mounted on slings
		Material	aluminum
	∐‡H	Color	
Α	В		RAL 9016 (white)
		Diffuser	OPTICS (optical system based on lenses)
		Impact resistant	IK04
		Dimensions [mm]	1425 x 48 x 70
A graph of light			105° 0°




Accessories


- Index 6E1-500KW34K-3
- Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 3X SET




- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB34K-3
- Name SUSPENSION NEW TYPE-A+E 34 LENGHT 1,5M WIRE 3X SET



