


Product: X-LINE SLIM L-DOWN LED 3250 OPTICS-ASYM EDD 04 830 / L-1425MM S-1,5M Index: 19.4090.4413.04



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information		
	Family X-LINE SLIM LED	
	Name X-LINE SLIM L-DOWN LED 3250 OPTICS-ASYM EDD 04 830 / L- 1425MM S-1,5M	
	Index 19.4090.4413.04	
	EAN 5902107551018	
	$\overbrace{LED} \textcircled{\begin{tabular}{ c c c c c } \hline \begin{tabular}{ c c c c } \hline \begin{tabular}{ c c c c c } \hline \begin{tabular}{ c c c c c c } \hline \begin{tabular}{ c c c c c c c } \hline \begin{tabular}{ c c c c c c c c c c c c c c c c c c c$	
Light and electrical data	Light source LED	
	Luminous flux LED [Im] 3172,5	
	LED power [W] 15,5	
	Luminaire luminous flux [Im] 2506,3	
	Power of luminaire [W] 17,6	
	Luminaire's light efficiency [Im/W] 142,4	
	Color of the light [K] 3000	
	CRI >80	
	SDCM (LED sources) 3	
	Beam angle [°] asymmetric light distribution - Imax=-20°	
	Photobiological risk class (IEC/EN RG0 62471)	
	Protection against electric shock	
	Protection degree IP40	
	Voltage 220240 V, 5060 Hz	
	Lifetime of LED sources [h] 100000	
	Lx/By L80/B10	
	Operating temperature range [°C] 5 ÷ 35	
	Driver DIM DALI (EDD)	
	Power factor cos φ >0,95	



Mechanical data	⊟tH B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) OPTICS (optical system based on lenses) IK04 1425 x 48 x 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 45° 45° 45° 45° 45° 45




Accessories

- Index 6E1-500KW04K-5
- Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 5X SET



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT








Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB04K-5
- Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 5X SET





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025