


## Product: X-LINE SLIM L-DOWN LED 5500 OPTICS-ASYM EDD 34 830 / L-1425MM S-1,5M Index: 19.4090.4713.34



## Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	Category Surface mounted luminaires		
	Family X-LINE SLIM LED		
	Name X-LINE SLIM L-DOWN LED 5500 OPTICS-ASYM EDD 34 830 . 1425MM S-1,5M		
	Index 19.4090.4713.34		
	EAN <b>5902107552749</b>		
	$\begin{array}{c} \hline \\ \hline $	ndoor	
Light and electrical data	Light source LED		
	Luminous flux LED [Im] 5552,5		
	LED power [W] 27,3		
	Luminaire luminous flux [Im] 4386,5		
	Power of luminaire [W] <b>31</b>		
	Luminaire's light efficiency [lm/W] 141,5		
	Color of the light [K] <b>3000</b>		
	CRI >80		
	SDCM (LED sources) 3		
	Beam angle [°] asymmetric light distributio Imax=-20°	on -	
	Photobiological risk class (IEC/EN <b>RG0</b> 62471)		
	Protection against electric shock		
	Protection degree IP40		
	Voltage 220240 V, 5060 Hz		
	Lifetime of LED sources [h] 100000		
	Lx/By <b>L80/B10</b>		
	Operating temperature range [°C] 5 ÷ 35		
	Driver DIM DALI (EDD)		
	Power factor cos φ >0,95		
	Circuit load capacity <b>17 (B10), 28 (B16), 26 (C10)</b> ,	, 41 (C16)	



Mechanical data		Assembly	surface mounted on slings
		Material	aluminum
	∐‡H	Color	
Α	В		RAL 9016 (white)
		Diffuser	OPTICS (optical system based on lenses)
		Impact resistant	IK04
		Dimensions [mm]	1425 x 48 x 70
A graph of light			105° 0°





## Accessories


- Index 6E1-500KW34K-5
- Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 5X SET



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB24K-5
- Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 5X SET

