


Product: X-LINE SLIM L-DOWN LED 2600 OPTICS-WIDE E 34 830 / L-1144MM S-1,5M Index: 19.4090.1311.34



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	Category Surface mounted luminaires		
r roudet miormation	Family X-LINE SLIM LED Name X-LINE SLIM L-DOWN LED 2600 OPTICS-WIDE E 34 830 / L- 1144MM S-1,5M		
	EAN 5902107550813		
	$\overbrace{LED} \textcircled{\begin{tabular}{c}{l}} \fbox{\begin{tabular}{c}{l}} \fbox{\begin{tabular}{c}{l}} \fbox{\begin{tabular}{c}{l}} \clubsuit{\begin{tabular}{c}{l}} \clubsuit{\begin{tabular}{c}} \clubsuit{\begin{tabular}{c}{l}} \begin{tab$	Indoor	
Light and electrical data	Light source LED		
	Luminous flux LED [Im] 2538		
	LED power [W] 12,4		
	Luminaire luminous flux [lm] 2106,5		
	Power of luminaire [W] 14,1		
	Luminaire's light efficiency [lm/W] 149,4		
	Color of the light [K] 3000		
	CRI >80		
	SDCM (LED sources) 3		
	Beam angle [°] (C0-C180) / (C90-C270) - 1 88,4°	101,8° /	
	Photobiological risk class (IEC/EN RG0 62471)		
	Protection against electric shock		
	Protection degree IP40		
	Voltage 220240 V, 5060 Hz		
	Lifetime of LED sources [h] 100000		
	Lx/By L80/B10		
	Operating temperature range [°C] 5 ÷ 35		
	Driver standard on/off (E)		
	Power factor $\cos \phi$ >0,95		
	Circuit load capacity 25 (B10), 40 (B16), 39 (C1	0), 62 (C16)	




Mechanical data	∏tH B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9016 (white) OPTICS (optical system based on lenses) IK04 1144 x 48 x 70
A graph of light			105° 90° 75° 60° 60° 45° 45° 300 45° 45° 45° 45° 45° 45° 45° 45°




Accessories

- Index 6E1-500KW34K-3
- Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 3X SET




- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB34K-3
- Name SUSPENSION NEW TYPE-A+E 34 LENGHT 1,5M WIRE 3X SET



