

Product: X-LINE SLIM L-DOWN LED 4400 OPTICS-WIDE E 34 840 / L-1144MM S-1,5M

Index: 19.4090.1621.34



## **Description**

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

### **Product information**

Category	Surface mounted luminaires
Family	X-LINE SLIM LED
Name	X-LINE SLIM L-DOWN LED 4400 OPTICS-WIDE E 34 840 / L- 1144MM S-1,5M
Index	19.4090.1621.34
EAN	5902107551926
















## Light and electrical data

Light source	LED	
Luminous flux LED [lm]	4676	
LED power [W]	21,8	
Luminaire luminous flux [lm]	3881,1	
Power of luminaire [W]	24,8	
Luminaire's light efficiency [lm/W]	156,5	
Color of the light [K]	4000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 101,8° / 88,4°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP40	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000	
Lx/By	L80/B10	
Operating temperature range [°C]	5 ÷ 35	
Driver	standard on/off (E)	
Power factor cos φ	>0,95	
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)	



Mechanical data		Assembly	surface mounted on slings
	□ ↓H B	Material	aluminum
A		Color	RAL 9016 (white)
		Diffuser	OPTICS (optical system based on lenses)
		Impact resistant	IK04
		Dimensions [mm]	1144 x 48 x 70

# A graph of light







### **Accessories**

Index 6E1-500KW34K-3

Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 3X SET



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Index 6E1-8670-B-1,5-3X

Name SUSPENSION NEW TYPE-F LENGHT-1,5 METER WIRE 3X 1-POINT




Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-500KWB34K-3

Name SUSPENSION NEW TYPE-A+E 34 LENGHT 1,5M WIRE 3X SET

