


Product: X-LINE SLIM L-DOWN LED 3250 OPTICS-WIDE E 04 840 / L-1425MM S-1,5M Index: 19.4090.2421.04



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	Category Surface mounted luminaires	Category Surface mounted luminaires		
	Family X-LINE SLIM LED			
	Name X-LINE SLIM L-DOWN LED 3250 OPTICS-WIDE E 04 840 / L 1425MM S-1,5M	-		
	Index 19.4090.2421.04			
	EAN 5902107551087			
	$\overbrace{LED} \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus_{Index} \bigoplus_{Index} \bigoplus$			
Light and electrical data	Light source LED			
	Luminous flux LED [Im] 3340			
	LED power [W] 15,5			
	Luminaire luminous flux [Im] 2772,2			
	Power of luminaire [W] 17,6			
	Luminaire's light efficiency [lm/W] 157,5			
	Color of the light [K] 4000			
	CRI >80			
	SDCM (LED sources) 3			
	Beam angle [°] (C0-C180) / (C90-C270) - 101, 88,4°	,8° /		
	Photobiological risk class (IEC/EN RG0 62471)			
	Protection against electric shock			
	Protection degree IP40			
	Voltage 220240 V, 5060 Hz			
	Lifetime of LED sources [h] 100000			
	Lx/By L80/B10			
	Operating temperature range [°C] 5 ÷ 35			
	Driver standard on/off (E)			
	Power factor cos φ >0,95			
	Circuit load capacity 25 (B10), 40 (B16), 39 (C10) ,	62 (C16)		



Mechanical data		Assembly	surface mounted on slings	
	‡H ++	Material	aluminum	
	l⊷i B	Color	RAL 9005 (black)	
		Diffuser	OPTICS (optical system based on lenses)	
		Impact resistant	IK04	
		Dimensions [mm]	1425 x 48 x 70	
A graph of light			h = 83%	




Accessories


- Index 6E1-500KW04K-3
- Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 3X SET



- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT









- Index 19.3272.1205.00
- Name SUSPENSION NEW TYPE-E
- LENGHT-1,5 METER WITHOUT WIRE 1-POINT



- Index 6E1-500KWB04K-3
- Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 3X SET

