


Product: X-LINE SLIM L-DOWN LED 3250 OPTICS-WIDE EDD 04 840 / L-1425MM S-1,5M Index: 19.4090.2423.04



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	C	Category Surface mounted luminaires			
	F	amily X-LINE SLIM LED			
	N	Name X-LINE SLIM L-DOWN LED 3250 OPTICS-WIDE EDD 04 840 / L- 1425MM S-1,5M			
	Ir	ndex 19.4090.2423.04			
	E	EAN 5902107551131			
		$\overbrace{LED} \textcircled{\ } \fbox{\ } \textcircled{\ } \swarrow{\ } $			
Light and electrical data	L	Light source LED			
		uminous flux LED [lm] 3340			
		ED power [W] 15,5			
		Luminaire luminous flux [lm] 2772,2			
	P	Power of luminaire [W] 17,6			
	L	uminaire's light efficiency [lm/W] 157,5			
	C	Color of the light [K] 4000			
	C	CRI >80			
	S	SDCM (LED sources) 3			
	В	Beam angle [°] (C0-C180) / (C90-C270) - 101,8° / 88,4°			
		Photobiological risk class (IEC/EN RG0 52471)			
	Ρ	Protection against electric shock			
	Ρ	Protection degree IP40			
	V	/oltage 220240 V, 5060 Hz			
	L	Lifetime of LED sources [h] 100000			
	L	_x/By L80/B10			
	C	Dperating temperature range [°C] 5 ÷ 35			
	D	Driver DIM DALI (EDD)			
	Р	Power factor cos φ >0,95			
	С	Circuit load capacity 17 (B10), 28 (B16), 26 (C10), 41 (C16)			



Mechanical data		Assembly	surface mounted on slings
A	‡H ++	Material	aluminum
	l⊷i B	Color	RAL 9005 (black)
		Diffuser	OPTICS (optical system based on lenses)
		Impact resistant	IK04
		Dimensions [mm]	1425 x 48 x 70
A graph of light			h = 83%




Accessories

- Index 6E1-500KW04K-5
- Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 5X SET



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT








Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB04K-5
- Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 5X SET





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025