


Product: X-LINE SLIM L-DOWN LED 3250 OPTICS-WIDE EDD 34 840 / L-1425MM S-1,5M Index: 19.4090.2423.34



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	Category Surface mounted luminaires
	Family X-LINE SLIM LED
	Name X-LINE SLIM L-DOWN LED 3250 OPTICS-WIDE EDD 34 840 / L- 1425MM S-1,5M
	Index 19.4090.2423.34
	EAN 5902107551179
	$\overbrace{LED} \textcircled{\bullet} \textcircled{\bullet} \textcircled{\bullet} \textcircled{\bullet} \textcircled{\bullet} \textcircled{\bullet} \textcircled{\bullet} $
Light and electrical data	Light source LED
	Luminous flux LED [Im] 3340
	LED power [W] 15,5
	Luminaire luminous flux [Im] 2772,2
	Power of luminaire [W] 17,6
	Luminaire's light efficiency [lm/W] 157,5
	Color of the light [K] 4000
	CRI >80
	SDCM (LED sources) 3
	Beam angle [°] (C0-C180) / (C90-C270) - 101,8° / 88,4°
	Photobiological risk class (IEC/EN RG0 62471)
	Protection against electric shock
	Protection degree IP40
	Voltage 220240 V, 5060 Hz
	Lifetime of LED sources [h] 100000
	Lx/By L80/B10
	Operating temperature range [°C] 5 ÷ 35
	Driver DIM DALI (EDD)
	Power factor cos φ >0,95
	Circuit load capacity 17 (B10), 28 (B16), 26 (C10), 41 (C16



Mechanical data	∏ ⊨≓ B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9016 (white) OPTICS (optical system based on lenses) IK04 1425 x 48 x 70
A graph of light			105° 90° 75° 60° 60° 45° 45° 45° 300 45° 30° 45° 45° 45° 45° 45° 45° 45° 45





Accessories


- Index 6E1-500KW34K-5
- Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 5X SET



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB24K-5
- Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 5X SET

