


Product: X-LINE SLIM L-DOWN LED 5500 OPTICS-WIDE E 04 830 / L-1425MM S-1,5M Index: 19.4090.2711.04



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information		Category Surface mounted luminaires		
		Family X-LINE SLIM LED		
		Name X-LINE SLIM L-DOWN LED 5500 OPTICS-WIDE E 04 830 / L- 1425MM S-1,5M		
		Index 19.4090.2711.04		
		EAN 5902107552763		
		$\overbrace{LED} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \end{array}{\end{array}}$		
Light and electrical data		Light source LED		
		Luminous flux LED [Im] 5552,5		
		LED power [W] 27,3		
		Luminaire luminous flux [Im] 4608,6		
		Power of luminaire [W] 31		
		Luminaire's light efficiency [lm/W] 148,7		
		Color of the light [K] 3000		
		CRI >80		
		SDCM (LED sources) 3		
		Beam angle [°] (C0-C180) / (C90-C270) - 101,8° / 88,4°		
		Photobiological risk class (IEC/EN RG0 62471)		
		Protection against electric shock I		
		Protection degree IP40		
		Voltage 220240 V, 5060 Hz		
		Lifetime of LED sources [h] 100000		
		Lx/By L80/B10		
		Operating temperature range [°C] 5 ÷ 35		
		Driver standard on/off (E)		
		Power factor cos φ >0,95		
		Circuit load capacity 25 (B10), 40 (B16), 39 (C10), 62 (C16)		



Mechanical data		Assembly	surface mounted on slings
	‡H ++	Material	aluminum
	В	Color	RAL 9005 (black)
		Diffuser	OPTICS (optical system based on lenses)
		Impact resistant	IK04
		Dimensions [mm]	1425 x 48 x 70
A graph of light			h = 83%




Accessories


- Index 6E1-500KW04K-3
- Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 3X SET



- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT









- Index 19.3272.1205.00
- Name SUSPENSION NEW TYPE-E
- LENGHT-1,5 METER WITHOUT WIRE 1-POINT



- Index 6E1-500KWB04K-3
- Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 3X SET

