


Product: X-LINE SLIM L-DOWN LED 5500 OPTICS-WIDE EDD 34 830 / L-1425MM S-1,5M Index: 19.4090.2713.34



## Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information		Category Surface mounted luminaires		
		Family X-LINE SLIM LED		
		Name X-LINE SLIM L-DOWN LED 5500 OPTICS-WIDE EDD 34 830 / L- 1425MM S-1,5M		
		Index 19.4090.2713.34		
		EAN <b>5902107552855</b>		
		$\overbrace{LED} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \end{array}{\end{array}}$		
Light and electrical data		Light source LED		
		Luminous flux LED [lm] 5552,5   LED power [W] 27,3		
		Luminaire luminous flux [Im] 4608,6		
		Power of luminaire [W] 31		
		Luminaire's light efficiency [Im/W] 148,7		
		Color of the light [K] <b>3000</b>		
		CRI >80		
		SDCM (LED sources) 3		
		Beam angle [°] (C0-C180) / (C90-C270) - 101,8° / 88,4°		
		Photobiological risk class (IEC/EN RG0 62471)		
		Protection against electric shock		
		Protection degree IP40		
		Voltage 220240 V, 5060 Hz		
		Lifetime of LED sources [h] 100000		
		Lx/By L80/B10		
		Operating temperature range [°C] 5 ÷ 35		
		Driver DIM DALI (EDD)		
		Power factor cos φ >0,95		
		Circuit load capacity 17 (B10), 28 (B16), 26 (C10), 41 (C16)		



Mechanical data	∏ ⊨≓ B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9016 (white) OPTICS (optical system based on lenses) IK04 1425 x 48 x 70
A graph of light			105° 90° 75° 60° 60° 45° 45° 45° 300 45° 30° 45° 45° 45° 45° 45° 45° 45° 45





## Accessories


- Index 6E1-500KW34K-5
- Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 5X SET



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB24K-5
- Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 5X SET

