


Product: X-LINE SLIM L-DOWN LED 2600 OPTICS-ASYM E 04 830 / L-1144MM S-1,5M Index: 19.4090.3311.04



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information	Category Surface mounted luminaires
	Family X-LINE SLIM LED
	Name X-LINE SLIM L-DOWN LED 2600 OPTICS-ASYM E 04 830 / L- 1144MM S-1,5M
	Index 19.4090.3311.04
	EAN 5902107550660
	$\overbrace{LED} \textcircled{} \end{array}{} \textcircled{} \end{array}{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \end{array}{\end{array}}$
Light and electrical data	Light source LED
	Luminous flux LED [Im] 2538
	LED power [W] 12,4
	Luminaire luminous flux [lm] 2005
	Power of luminaire [W] 14,1
	Luminaire's light efficiency [lm/W] 142,2
	Color of the light [K] 3000
	CRI >80
	SDCM (LED sources) 3
	Beam angle [°] asymmetric light distribution - Imax=-20°
	Photobiological risk class (IEC/EN RG0 62471)
	Protection against electric shock I
	Protection degree IP40
	Voltage 220240 V, 5060 Hz
	Lifetime of LED sources [h] 100000
	Lx/By L80/B10
	Operating temperature range [°C] 5 ÷ 35
	Driver standard on/off (E)
	Power factor cos φ >0,95
	Circuit load capacity 25 (B10), 40 (B16), 39 (C10), 62 (C1



Mechanical data		Assembly	surface mounted on slings
	<u> </u> H ⊨I	Material	aluminum
A	В	Color	RAL 9005 (black)
		Diffuser	OPTICS (optical system based on lenses)
		Impact resistant	IK04
		Dimensions [mm]	1144 x 48 x 70
A graph of light			105° 105° 90° 90° 75° 200 60° 200 45° 60° 45° 60° 30° 15° 30° 15° 30° 15° 30° 15° 0° 15° <




Accessories


- Index 6E1-500KW04K-3
- Name SUSPENSION NEW TYPE-A+B 04 LENGHT 1,5M WIRE 3X SET



- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT









- Index 19.3272.1205.00
- Name SUSPENSION NEW TYPE-E
- LENGHT-1,5 METER WITHOUT WIRE 1-POINT



- Index 6E1-500KWB04K-3
- Name SUSPENSION NEW TYPE-A+E 04 LENGHT 1,5M WIRE 3X SET

