


Product: X-LINE SLIM L-DOWN LED 4400 OPTICS-ASYM EDD 21 840 / L-1144MM S-1,5M Index: 19.4090.3623.21



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information		Category Surface mounted luminaires		
		Family X-LINE SLIM LED		
		Name X-LINE SLIM L-DOWN LED 4400 OPTICS-ASYM EDD 21 840 / L- 1144MM S-1,5M		
		Index 19.4090.3623.21		
		EAN 5902107551858		
		$\underbrace{}_{\text{LED}} \underbrace{}_{\text{ED}} \underbrace{}_{\text{ED}} \underbrace{}_{\text{Ho}} \overset$		
Light and electrical data		Light source LED		
		Luminous flux LED [Im] 4676		
		LED power [W] 21,8		
		Luminaire luminous flux [Im] 3694		
		Power of luminaire [W] 24,8		
		Luminaire's light efficiency [Im/W] 149		
		Color of the light [K] 4000		
		CRI >80		
		SDCM (LED sources) 3		
		Beam angle [°] asymmetric light distribution - Imax=-20°		
		Photobiological risk class (IEC/EN RG0 62471)		
		Protection against electric shock		
		Protection degree IP40		
		Voltage 220240 V, 5060 Hz		
		Lifetime of LED sources [h] 100000		
		Lx/By L80/B10		
		Operating temperature range [°C] 5 ÷ 35		
		Driver DIM DALI (EDD)		
		Power factor cos φ >0,95		
		Circuit load capacity 17 (B10), 28 (B16), 26 (C10), 41 (C16)		



Mechanical data	□H B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9006 (grey) OPTICS (optical system based on lenses) IK04 1144 x 48 x 70
A graph of light			105° 90° 90° 60° 45° 45° 45° 45° 400 45° 40° 45° 40° 45° 40° 45° 40° 45° 40° 45° 40° 45° 40° 45° 40° 45° 40° 45° 45° 45° 45° 45° 45° 45° 45° 45° 45



Accessories


Index 6E1-500KWANK-5 Name SUSPENSION NEW TYPE-A+B 24



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



Index 6E1-8670-B-1,5-5X
Name SUSPENSION NEW TYPE-F
LENGHT-1,5 METER WIRE 5X 1POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 19.3272.1205.00

- Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 6E1-500KWB24K-5

Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 5X SET



