

**Product:** PATOS O120 LED 19600 PLX EDD 840

**Index:** 19.4094.6723.34



## Description

Nowadays architectural lighting should embody an irreproachable style and high quality of lighting parameters. A luminaire is expected to be exceptional in respect of its design – simple and elegant. Patos is designed for lighting galleries, museums, offices, clubs, restaurants and hotels; it gives any interior individual modern character. Fitting designed for suspended plasterboard ceilings, adapted to befit the ceiling surface. Body made of aluminium profile, prismatic diffuser with very good light transmission coefficient and light diffusion parameters. Mounting should take place before the ceiling surface is finished. After the finishing work of the ceiling is ended, the diffuser is installed.

## Product information



Category	Architectural luminaires
Family	PATOS O LED
Name	PATOS O120 LED 19600 PLX EDD 840
Index	19.4094.6723.34
EAN	5902107198640



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	19600
LED power [W]	147
Luminaire luminous flux [lm]	14196
Power of luminaire [W]	169
Luminaire's light efficiency [lm/W]	84
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 112,8° / 113,8°
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	4 (B10), 6 (B16), 6 (C10), 10 (C16)

## Mechanical data



Assembly	mounted in plasterboard ceilings
Material	steel sheet
Color	white
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	22,81
Dimensions [mm]	Ø1222 x 164
Mounting hole [mm]	Ø1226

A graph of light

