

Product: PATOS O65 LED 4600 PLX EDD 927-965 / TUNABLE WHITE

Index: 19.4094.2363.34



## **Description**

Nowadays architectural lighting should embody an irreproachable style and high quality of lighting parameters. A luminaire is expected to be exceptional in respect of its design — simple and elegant. Patos is designed for lighting galleries, museums, offices, clubs, restaurants and hotels; it gives any interior individual modern character. Fitting designed for suspended plasterboard ceilings, adapted to befit the ceiling surface. Body made of aluminium profile, prismatic diffuser with very good light transmission coefficient and light diffusion parameters. Mounting should take place before the ceiling surface is finished. After the finishing work of the ceiling is ended, the diffuser is installed. LED modules adjusted to regulate the color temperature of light in the range from 2700 K to 6500 K.

### **Product information**

Category	Architectural luminaires
Family	PATOS O LED
Name	PATOS O65 LED 4600 PLX EDD 927-965 / TUNABLE WHITE
Index	19.4094.2363.34
EAN	5902107307387















## Light and electrical data

Light source	LED
Luminous flux LED [lm]	4650
LED power [W]	29,9
Luminaire luminous flux [lm]	3368
Power of luminaire [W]	33,5
Luminaire's light efficiency [lm/W]	100,5
Color of the light [K]	2700 ÷ 6500
CRI	>90
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 112,8° / 113,8°
Protection against electric shock	I
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 80000 (2)
Lx/By	L70/B10 (1) / L80/B10 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor $\cos \phi$	>0,95
Circuit load capacity	13 (B10), 22 (B16), 21 (C10), 36 (C16)

### Mechanical data



\_\_\_\_\_t<sub>H</sub>

Assembly	mounted in plasterboard ceilings
Material	steel sheet
Color	white
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	Ø672 x 150
Mounting hole [mm]	Ø676



# A graph of light



