

### Product: FLYING SURFACE LED 6400 E 34 840 Index: 19.4098.1121.34



## Description

Luminary body made from steal sheet powder coated with thermostatic mixture of the synthetic solid resin, hardeners, and pigments what makes it UV radiation resistant. The outer finishing of the luminary is a layer of a white fabric which is based on PCV. The fabric diffuser is placed in a steal frame, which is coated in white and covered with the white fabric. The frame is mounted to the luminary body by hidden brackets. Its mounting and dismantling performed without any extra tools. One of the most outstanding attributes of Flying Surface LED is the optical effect produced by a luminous surface floating in space. Mounting directly on walls or ceilings by special brackets. It is also possible to Mount the luminary on special suspensions which provide the smooth regulation of the luminary height. These are made from steel cables and are 1500mm long.

(C16)

Product information	Category	Architectural lumir	naires
Product mormation	Family	FLYING SURFACE	
	Name	FLYING SURFACE	
			LED 6400 E 34 840
	Index	19.4098.1121.34	
Light and electrical data	Light sourc	e	LED
	Luminous f	lux LED [lm]	5940
	LED power	[W]	46
	Luminaire I	uminous flux [lm]	3244
	Power of lu	minaire [W]	50
	Luminaire's	s light efficiency [lm/W]	64,9
	Color of the	e light [K]	4000
	CRI		>80
	SDCM (LEI	D sources)	3
	Beam angle [°]		(C0-C180) / (C90-C270) - 107° / 107°
	Photobiolog 62471)	gical risk class (IEC/EN	RG0
	Protection	against electric shock	I
	Protection	degree	IP20
	Voltage		220240 V, 5060 Hz
	Lifetime of	LED sources [h]	100000
	Lx/By		L80/B10
	Operating t	emperature range [°C]	5 ÷ 30
	Driver		standard on/off (E)
	Power facto	or cos φ	>0,95
	Circuit load	capacity	16 (B10), 26 (B16), 23 (C10), 37



# Mechanical data Assembly directly mounted to ceiling construction or surface mounted on slings using accessories Material steel sheet Color RAL 9016 (white)



Assembly	directly mounted to ceiling construction or surface mounted on slings using accessories
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	white fabric based on PCV
Impact resistant	IK04
Weight [kg]	10,5
Dimensions [mm]	740 x 740 x 60

# A graph of light



## Accessories

#### Index 19.3272.1205.00 Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-500OKW1P-3

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 3X 1-POINT

