

Product: EUROPANEL LED 3800 MICRO-PRM EDD IP20/44 34 840 1200X300

Index: 19.4099.2123.34



## Description

Modern LED panel for installation in suspended ceilings or directly on the ceiling. Equipped with the highly efficient LED sources. Luminary body made from aluminum. PMMA opal diffuser. Colour of luminary - white. Luminary dedicated for the public use structure like offices, conference rooms, classrooms, lecture halls etc.

## Product information

Category	Recessed luminaires
Family	EUROPANEL LED
Name	EUROPANEL LED 3800 MICRO-PRM EDD IP20/44 34 840 1200X300
Index	19.4099.2123.34
EAN	5902107169886



## Light and electrical data


Light source	LED
Luminous flux LED [lm]	3653
LED power [W]	19,3
Luminaire luminous flux [lm]	2575
Power of luminaire [W]	21
Luminaire's light efficiency [lm/W]	122,6
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 91,8° / 94,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	II
Protection degree	IP20/44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 80000 (2)
Lx/By	L70/B10 (1) / L80/B10 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	12 (B10), 20 (B16), 20 (C10), 32 (C16)

## Mechanical data



Assembly	mounted in module ceilings, plasterboard ceilings (using accessories) or surface mounted (using accessories)
Material	aluminum
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	1196 x 296 x 11


## A graph of light



## Accessories

Index 01ARTLUGK-AW

Name EUROPANEL / RIM COMPACT  
LED ADAPTIVE PLASTERBOARD  
CEILING FRAME 34 / 1200X300



Index 01ARTLURNNW12

Name EUROPANEL / RIM COMPACT  
LED CEILING ADAPTIVE FRAME  
STANDARD 34 / 1200X300



Index 19.3247.0013.34

Name EUROPANEL / RIM COMPACT  
LED SURFACE ACCESSORIES  
BASIC 34 / 1200X300

