

**Product:** EUROPANEL LED 8000 MICRO-PRM EDD IP20/44 34 840 1200X300

**Index:** 19.4099.2423.34



## Description

Modern LED panel for installation in suspended ceilings or directly on the ceiling. Equipped with the highly efficient LED sources. Luminaire body made from aluminum. PMMA opal diffuser. Colour of luminaire - white. Luminaire dedicated for the public use structure like offices, conference rooms, classrooms, lecture halls etc.

## Product information

Category	Recessed luminaires
Family	EUROPANEL LED
Name	EUROPANEL LED 8000 MICRO-PRM EDD IP20/44 34 840 1200X300
Index	19.4099.2423.34
EAN	5902107330910



## Light and electrical data


Light source	LED
Luminous flux LED [lm]	9839
LED power [W]	53,1
Luminaire luminous flux [lm]	6936
Power of luminaire [W]	59
Luminaire's light efficiency [lm/W]	117,6
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 91,8° / 94,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	II
Protection degree	IP20/44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	70000 (1) / 56000 (2)
Lx/By	L70/B10 (1) / L80/B10 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,98
Circuit load capacity	10 (B10), 16 (B16), 16(C10), 26 (C16)

Mechanical data




Assembly	mounted in module ceilings, plasterboard ceilings (using accessories) or surface mounted (using accessories)
Material	aluminum
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Weight [kg]	3,04
Dimensions [mm]	1196 x 296 x 11

A graph of light



Accessories

Index	01ARTLUGK-AW
Name	EUROPANEL / RIM COMPACT LED ADAPTIVE PLASTERBOARD CEILING FRAME 34 / 1200X300
	

Index	01ARTLURNNW12
Name	EUROPANEL / RIM COMPACT LED CEILING ADAPTIVE FRAME STANDARD 34 / 1200X300
	

Index	19.3247.0013.34
Name	EUROPANEL / RIM COMPACT LED SURFACE ACCESSORIES BASIC 34 / 1200X300
	