

Product: EUROPANEL LED 5800 PLX EDD IP20/44 34 840 600X600

Index: 19.4099.3323.34



Description

Modern LED panel for installation in suspended ceilings or directly on the ceiling. Equipped with the highly efficient LED sources. Luminary body made from aluminum. PMMA opal diffuser. Colour of luminary - white. Luminary dedicated for the public use structure like offices, conference rooms, classrooms, lecture halls etc.

Product information

| Category | Recessed luminaires |
|----------|---|
| Family | EUROPANEL LED |
| Name | EUROPANEL LED 5800 PLX EDD IP20/44 34 840 600X600 |
| Index | 19.4099.3323.34 |
| EAN | 5902107145477 |
















Light and electrical data

| Light source | LED |
|--|---|
| Luminous flux LED [lm] | 6508 |
| LED power [W] | 40,5 |
| Luminaire luminous flux [lm] | 4712 |
| Power of luminaire [W] | 45,6 |
| Luminaire's light efficiency [lm/W] | 103,3 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 115,4° / 107,6° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| | |
| Protection against electric shock | II |
| Protection against electric shock Protection degree | II IP20/44 |
| | •• |
| Protection degree | IP20/44 |
| Protection degree Voltage | IP20/44 220240 V, 5060 Hz |
| Protection degree Voltage Lifetime of LED sources [h] | IP20/44 220240 V, 5060 Hz 100000 (1) / 80000 (2) |
| Protection degree Voltage Lifetime of LED sources [h] Lx/By | IP20/44 220240 V, 5060 Hz 100000 (1) / 80000 (2) L70/B10 (1) / L80/B10 (2) |
| Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C] | IP20/44 220240 V, 5060 Hz 100000 (1) / 80000 (2) L70/B10 (1) / L80/B10 (2) 5 ÷ 30 |




Mechanical data



| Assembly | mounted in module ceilings, plasterboard ceilings (using accessories) or surface mounted (using accessories) |
|------------------|--|
| Material | aluminum |
| Color | RAL 9016 (white) |
| Diffuser | PLX (PMMA opal) |
| Impact resistant | IK04 |
| Weight [kg] | 3,61 |
| Dimensions [mm] | 596 x 596 x 11 |

A graph of light



Accessories

Index 2C1A7392-34R

Name EUROPANEL / BACKPANEL / RIM COMPACT LED RECESSED ACCESSORIES 34 / 600X600



Index 01ARTLUNCNW6

Name EUROPANEL / RIM COMPACT LED SURFACE ACCESSORIES STANDARD 34 / 600X600



Index 01ARTBLUNCNW6

Name EUROPANEL / RIM COMPACT LED SURFACE ACCESSORIES BASIC 34 / 600X600x43mm

